

County Surveyor's Record, Douglas County, Oregon

Subdivision of Section 7, T. 33 S., R. 6 W.

CHAINS

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins. in the ground, with brass cap mkd.

C $\frac{1}{4}$
S 7
1964

from which

An incense cedar, 12 ins. diam., bears N. $17\frac{1}{2}^{\circ}$ E., 74 lks. dist., mkd. C $\frac{1}{4}$ S7 BT.

An incense cedar, 8 ins. diam., bears N. 70° W., 20 lks. dist., mkd. C $\frac{1}{4}$ S7 BT.

Ascend 25 ft. over SE. slope.

43.50 Spur, slopes E.; desc. 215 ft. over NE. slope.

57.80 Head of swale, drains E.; asc. 10 ft. over SE. slope.

59.01 Point for the center N $1/16$ sec. cor. of sec. 7.

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 26 ins. in the ground, with brass cap mkd.

N $1/16$ $\begin{array}{c} C \\ | \\ S 7 \\ | \\ C \end{array}$
1964

from which

A Douglas fir, 12 ins. diam., bears N. 9° E., 69 lks. dist., mkd. CN $1/16$ S7 BT.

An incense cedar, 14 ins. diam., bears N. 66° W., 99 lks. dist., mkd. CN $1/16$ S7 BT.

Corner falls on a spur, slopes E.; desc. 25 ft. over NE. slope.

63.95 Ravine, drains E.; asc. 240 ft. over SE. slope.

78.64 The $\frac{1}{4}$ sec. cor. of secs. 6 and 7.

Land, mountainous.

Soil, rocky clay.

Timber, Douglas fir and incense cedar; undergrowth, vine maple, chinquapin, oak, and madrone.

From the $\frac{1}{4}$ sec. cor. of secs. 7 and 8.

S. $88^{\circ} 43'$ W., on the E. and W. center line of sec. 7.

Ascend 470 ft. over SE. slope.

20.00 Point for the center E $1/16$ sec. cor. of sec. 7.

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.

E $1/16$ C
S 7
1964

from which