

# County Surveyor's Record, Douglas County, Oregon

Remonumentation, Original Corner Points, T. 33 S., R. 6 W.

CHAINS

East Boundary, T. 33 S., R. 6 W.  
Willamette Meridian, Oregon

(Remonumenting the corner established by Butler Ives and George W. Hyde in 1854, reported by Williams Byars in 1882, and rehabilitated by Edward F. Sharp in 1894.)

The cor. of secs. 19, 24, 25 and 30, on the E. bdy. of the Twp., determined from a bearing tree marked by Edward F. Sharp, in 1894:

A sawed Douglas fir stump, 28 ins. diam., bears S. 81° E., 67 lks. dist., mkd. T33S R5W S30 BT on opened blaze.


and locally established bearing trees

A Douglas fir snag, 28 ins. diam., bears S. 81° E., 22 lks. dist., mkd. S30 T33S R5W BT 1543.

A Douglas fir, dead and down, 12 ins. diam., bears N. 82° W., 75 lks. dist., mkd. S25 T33S R6W BT 1543.

At the corner point

Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.



from which

A Douglas fir, 4 ins. diam., bears N. 43° E., 78 lks. dist., mkd. XBT.

A Douglas fir, 20 ins. diam., bears S. 53½° E., 60½ lks. dist., mkd. T33S R5W S30 BT.

A Douglas fir, 13 ins. diam., bears S. 24° W., 73½ lks. dist., mkd. T33S R6W S25 BT.

A Douglas fir, 8 ins. diam., bears N. 48° W., 69 lks. dist., mkd. T33S R6W S24 BT.

(Remonumenting the corners established by Butler Ives and George W. Hyde in 1854)

The cor. of Twps. 33 and 34, S., Rs. 5 and 6 W., monumented with a basalt stone, 18 x 18 x 10 ins. firmly set in a mound of stone, 3 ft. base, to top, marked with a cross on top, from which the remains of the original bearing trees:

A Douglas fir stump, size indeterminate, bears N. 24° E., 76 lks. dist., with a burned face.

A Douglas fir stump, size indeterminate, bears S. 57° E., 53 lks. dist., with a burned blaze.

A Douglas fir stump, size indeterminate, bears S. 72° W., 72 lks. dist., with a burned blaze.