

County Surveyor's Record, Douglas County, Oregon

Remonumentation, Original Corner Points, T. 33 S., R. 6 W.

CHAINS

A Douglas fir snag, 48 ins. diam., bears
N. 38° W., 38 lks. dist., mkd. R6W on
burned blaze.

and a bearing tree mkd. by R. Templin, Registered
Engineer, No. 3024.

A Douglas fir snag, 20 ins. diam., bears S. 27° E.,
16 lks. dist., mkd. S6 RE 3024 BT.

At the corner point

Set an iron post, 30 ins. long, 2 $\frac{1}{2}$ ins. diam., 20 ins.
in the ground, and in a mound of stone, 4 ft. base, to
top, with brass cap mkd.

T 33 S	
R 6 W	R 5 W
S 36	S 31
S 1	S 6
T 34 S	
1963	

from which

The face of a conglomerate outcrop, 10 x 6 ft.,
bears S. 89° E., 211 lks. dist., mkd. BXO.

The madrone 6 ins. diam., bears S. 87° W.,
38 lks. dist., mkd. T34S R6W S1 BT.

A madrone, 6 ins. diam., bears N. 62° W., 37 lks.
dist., mkd. T33S R6W S36 BT.

There is no tree or bearing object available
within limits in the NE. quadrant.

Reset corner stone on South side of iron post.

South Boundary, T. 33 S., R. 6 W.

(Remonumenting corners established by Wells Lake
and George W. Hyde, in 1855.)

The $\frac{1}{4}$ sec. cor. of secs. 2 and 35, monumented with an
iron pipe, $\frac{1}{2}$ in. diam., inserted in an iron pipe, 1 $\frac{1}{2}$ ins.
diam., firmly set, protruding 8 ins. above the ground,
from which the original bearing trees:

A black oak, 26 ins. diam., bears N. 30° E.,
100 lks. dist., mkd. 4 B on opened rotted
blaze.

A white oak, 32 ins. diam., bears S. 24° E.,
70 lks. dist., mkd. $\frac{1}{4}$ S on opened blaze.

and locally established bearing trees

A white oak, 9 ins. diam., bears N. 65 $\frac{1}{2}$ ° W.,
20 lks. dist., mkd. $\frac{1}{4}$ S35 RS 404 BT on
partially healed blaze.

A white oak, 10 ins. diam., bears S. 21° E.,
14 $\frac{1}{2}$ lks. dist., mkd. $\frac{1}{4}$ S2 RS 404 BT on
partially healed blaze.