

## County Surveyor's Record, Douglas County, Oregon

Remonumentation, Original Corner Points, T. 33 S., R. 6 W.

CHAINS

U		
S	T 33 S	R 6 W
B	S 31	S 32
L	S 6	S 5
M	1963	

from which

A Douglas fir, 12 ins. diam., bears N. 15° E.,  
67½ lks. dist., mkd. T33S R6W S32 BT.

A Douglas fir, 8 ins. diam., bears S. 62½° E.,  
67 lks. dist., mkd. T34S R6W S5 BT.

A Douglas fir, 12 ins. diam., bears S. 31° W.,  
125 lks. dist., mkd. T34S R6W S6 BT.

A Douglas fir, 6 ins. diam., bears N. 4° W.,  
81½ lks. dist., mkd. T33S R6W S31 BT.

From this point an iron pipe 1½ ins. diam., firmly  
set, protruding 10 ins. above the ground, bears  
S. 75½° W., 48 lks. dist.

The ¼ sec. cor. of secs. 6 and 31, on the S. bdy. of  
the Twp., monumented with an iron pipe, 1 in. diam.,  
firmly set, protruding 6 ins. above the ground, from  
which the remaining original bearing tree:

A black oak, 24 ins. diam., bears S. 78° W.,  
221 lks. dist., mkd. BT on opened blaze.

and a locally established bearing tree

A ponderosa pine, 24 ins. diam., bears N. 66° E.,  
90½ lks. dist., mkd. ¼ S31 BT on partially  
headed blaze.

At the corner point

Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins.  
in the ground, with brass cap mkd.

	T 33 S	R 6 W
¼	S 31	
	S 6	
	T 34 S	
	1963	

from which

A Douglas fir, 6 ins. diam., bears N. 30½° E.,  
146½ lks. dist., mkd. ¼ S31 BT.

A Douglas fir, 6 ins. diam., bears S. 64° E.,  
84½ lks. dist., mkd. ¼ S6 BT.

Insert iron pipe inside iron post.

The cor. of Twps. 33 and 34 S., Rs. 6 and 7 W., monumented  
with an iron pipe, 3 ins. diam., firmly set, protruding  
5 ins. above the ground, from which the remains of the  
Original bearing trees;

A ponderosa pine, dead, down and burned, size  
indeterminate, bears N. 15° E., 46 lks. dist.,  
with no marks remaining.