

County Surveyor's Record, Douglas County, Oregon

Remonumentation, Original corner Points, T. 33 S., R. 6 W.

CHAINS

A black oak stump, size indeterminate, bears S. 80° E., 41 lks. dist., with no marks remaining.

A ponderosa pine, dead and down, 36 ins. diam., bears S. 41° W., 83 lks. idst., with a burned blaze and old axe marks.

A black oak, dead and down, 14 ins. diam., bears N. 89° W., 66 lks. dist., with a burned and rotted blaze.

and a line tree

A Douglas fir, 40 ins. diam., bears South, 9 lks. dist., with two hacks on the North and two hacks on the South side.

and bearing trees marked by Marvin C. Ramsey, Registered Surveyor No. 404.

A black oak, 16 ins. diam., bears N. 50° E., 91 lks. dist., mkd. T33S R6W S31 RS 404 BT.

A black oak, 18 ins. diam., bears S. 88° E., 110 lks. dist., mkd. T34S R6W S6 RS 404 BT.

At the corner point

Set a brass tablet, 3¼ ins. diam., 3½ in. stem, in concrete, in the iron pipe, with top mkd.

T 33 S	
R 7 W	R 6 W
S 36	S 31
S 1	S 6
T 34 S	
1963	

from which

A Douglas fir, 20 ins. diam., bears S. 72½° W., 135 lks. dist., mkd. T34S R7W S1 BT.

West Boundary, T. 33 S., R. 6 W.

(Remonumenting corners established by Lake and Hyde in 1855)

The cor. of secs. 25, 30, 31 and 36, on the W. bdy. of the Twp., determined from the remains of two original bearing trees:

A sawed Douglas fir stump, 22 ins. diam., bears N. 49° E., 42 lks. dist., mkd. SBT on exposed portion of blaze.

A maple, 20 ins. diam., bears S. 26° W., 15 lks. dist., with a chopped and obliterated blaze.

At the corner point