

County Surveyor's Record, Douglas County, Oregon

Remonumentation, Original Corner Points, T. 33 S., R. 6 W.

CHAINS

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.

T 33 S	
R 7 W	R 6 W
S 25	S 30
S 36	S 31
1963	

from which

- A Douglas fir, 9 ins. diam., bears N. $8\frac{1}{2}^{\circ}$ E., 16 lks. dist., mkd. T33S R6W S30 BT.
- A Douglas fir, 21 ins. diam., bears S. 20° E., 94 lks. dist., mkd. T33S R6W S31 BT.
- A yew, 8 ins. diam. bears S. 36° W., 56 lks. dist., mkd. T33S R7W S36 BT.
- A forked alder, 35 ins. diam., bears N. $46\frac{1}{2}^{\circ}$ W., 20 lks. dist., mkd. T33S R7W S25 BT.

The cor. of secs. 13, 18, 19 and 24, on the W. bdy. of the Twp., determined from three original bearing trees:

- A Douglas fir, 50 ins. diam., bears N. 52° E., 19 lks. dist., mkd. T33S R6W S18 on opened blaze.
- A black oak, 24 ins. diam., bears S. 74° E., 75 lks. dist., with a rotted blaze, no marks remaining.
- A live oak stool, bears S. 10° W., 3 lks. dist.

At the corner point

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.

T 33 S	
R 7 W	R 6 W
S 13	S 18
S 24	S 19
1963	

from which

- A forked black oak, 36 ins. diam., bears N. 26° E., 111 lks. dist., mkd. T33S R6W S18 BT.
- A Douglas fir, 6 ins. diam., bears S. 41° E., 106 lks. dist., mkd. T33S R6W S19 BT.
- A black oak, 6 ins. diam., bears S. 18° W., 48 lks. dist., mkd. T33S R7W S24 BT.
- A madrone, 6 ins. diam., bears N. 20° W., $46\frac{1}{2}$ lks. dist., mkd. T33S R7W S13 BT.

Subdivisions, T. 33 S., R. 6 W.

(Remonumenting corners established by
Lake and Hyde in 1855)