

County Surveyor's Record, Douglas County, Oregon

Remonumentation, Original Corner Points, T. 33 S., R. 6 W.

CHAINS

The $\frac{1}{4}$ sec. cor. of secs. 23 and 24, rmonumented with a solid iron rod, $1\frac{1}{2}$ ins. diam., firmly set, protruding 2 ins. above the ground, recorded by Fred Mensch. County Surveyor, in 1909, from which the remaining original bearing tree:

A white oak, 30 ins. diam., bears S. 81° E., 110 lks. dist., with rotted blaze.

and a bearing tree marked by Fred Mensch

A white oak, 10 ins. diam., bears S. 53° W., 30 lks. dist., mkd. CS on partially healed blaze.

At the corner point

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins. in the ground, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.

T 33 S R 6 W
 $\frac{1}{4}$
 S 23 | S 24
 1963

from which

A black oak, 6 ins. diam., bears S. 32° E., $13\frac{1}{2}$ lks. dist., mkd. $\frac{1}{4}$ S 24 BT.

A Douglas fir, 8 ins. diam., bears S. 30° W., 58 lks. dist., mkd. $\frac{1}{4}$ S23 BT.

Reset iron rod flush with the ground alongside iron post,

The cor. of secs. 4, 5, 8 and 9, monumented with an iron pipe, $1\frac{1}{2}$ ins. diam., firmly set, protruding 14 ins. above the ground, from which the remains of the original bearing trees:

An incense cedar snag, 26 ins. diam., bears North 8° E., 24 lks. dist., with scribe marks 4 BT visible on partially healed and weathered blaze.

A sawed Douglas fir stump, 24 ins. diam., bears S. 40° E., 40 lks. dist., with scribe marks BT visible on exposed blaze.

A sawed Douglas fir stump, 18 ins. diam., bears S. 60° W., 98 lks. dist., with scribe marks BT visible on exposed blaze.

An incense cedar snag, 16 ins. diam., bears N. 23° W., 14 lks. dist., with no marks remaining. (Record, N. 43° W.)

At the corner point

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 26 ins. in the ground, with brass cap mkd.

T 33 S R 6 W
 S 5 | S 4
 S 8 | S 9
 1963

FD. OK 4/84
 R. THOMPSON
 R.M. 3-61