

## County Surveyor's Record, Douglas County, Oregon

Remonumentation, Original Corner Points, T. 33 S., R. 6 W.

CHAINS

from which

A ponderosa pine, 8 ins. diam., bears N. 25° E.,  
50 lks. dist., mkd. T33S R6W S4 BT.

A Douglas fir, 6 ins. diam., bears S. 13° E.,  
31 lks. dist., mkd. T33S R6W S9 BT.

A ponderosa pine, 8 ins. diam., bears S. 34° W.,  
29 lks. dist., mkd. T33S R6W S8 BT.

A Douglas fir, 6 ins. diam., bears N. 45° W.,  
24½ lks. dist., mkd. T33S R6W S5 BT.

Insert iron pipe inside iron post.

Subdivisions, T. 33 S., R. 6 W.

(Remonumenting corners established by  
William Byars in 1882)

The ¼ sec. cor. of secs. 24 and 25, monumented with an  
iron rod, 1½ ins. diam., firmly set, protruding 4 ins.  
above the ground, from which the remains of the original  
bearing trees:

A rotted Douglas fir stump, 10 ins. diam., bears  
N. 10° E., 23 lks. dist., with axe marks.

A Douglas fir stump, size indeterminate, bears  
S. 4° E., 18 lks. dist., with no marks remaining.

At the corner point

Set an iron post, 30 ins. long, 2½ ins. diam., 22 ins.  
in the ground, with brass cap mkd.

$$\frac{1}{4} \begin{array}{c} S \ 24 \\ S \ 25 \\ T \ 33 \ S \ R \ 6 \ W \\ 1963 \end{array}$$

from which

A Douglas fir, 10 ins. diam., bears N. 78° E.,  
28 lks. dist., mkd. ¼ S24 BT.

A Douglas fir, 12 ins. diam., bears S. 6½° E.,  
34 lks. dist., mkd. ¼ S25 BT..

Insert iron rod inside iron post.

The ¼ sec. cor. of secs. 32 and 33, monumented with an  
iron pipe, 1½ ins. diam., firmly set, protruding 8 ins.  
above the ground, from which the remains of the original  
bearing trees:

A black oak, dead and down, 8 ins. diam., bears  
S. 35° E., 48 lks. dist., with scribe marks S BT  
visible on weathered blaze.

A black oak, 24 ins. diam., bears N. 26° W.,  
56 lks. dist., with a rotted blaze, no marks  
remaining.