

County Surveyor's Record, Douglas County, Oregon

Remonumentation, Original Corner Points, T. 33 S., R. 6 W.

CHAINS

At the corner point

Set an iron post, 30 ins. long, 2½ ins. diam., 26 ins. in the ground, with brass cap mkd.

T. 33 S. R 6 W
 $\frac{1}{4}$
 S 32 | S 33
 1963

from which

A Douglas fir, 9 ins. diam., bears S. 69° E.,
 33½ lks. dist., mkd. $\frac{1}{4}$ S33 BT.

A Douglas fir, 8 ins. diam., bears S. 22° W.,
 43 lks. dist., mkd. $\frac{1}{4}$ S32 BT.

Insert iron pipe inside iron post.

The $\frac{1}{4}$ sec. cor. of secs. 31 and 32, monumented with an iron pipe, 1 in. diam., an iron bolt, $\frac{1}{2}$ in. diam., 12 ins. long, inside the iron pipe, firmly set, protruding 7 ins. above the ground, from which the original bearing trees:

A black oak, 16 ins. diam., bears N. 74° W.,
 36 lks. dist., with scribe marks $\frac{1}{4}$ S BT visible on weathered blaze.

A black oak, 18 ins. diam., bears S. 55° E.,
 37 lks. dist., with scribe marks $\frac{1}{4}$ S visible on weathered and partially healed blaze.

At the corner point

Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

T 33 S R 6 W
 $\frac{1}{4}$
 S 31 | S 32
 1963

from which

A Douglas fir, 12 ins. diam., bears N. 44° E.,
 43 lks. dist., mkd. $\frac{1}{4}$ S32 BT.

A Douglas fir, 10 ins. diam., bears S. 48° W.,
 27½ lks. dist., mkd. $\frac{1}{4}$ S31 BT.

Insert iron pipe and iron bolt inside iron post.

The $\frac{1}{4}$ sec. cor. of secs. 30 and 31, monumented with the original corner tree, a Douglas fir, 20 ins. diam. mkd. $\frac{1}{4}$ S on North face of opened blaze, from which the remains of the original bearing trees:

Fragments of a black oak, bears North, 28 lks. dist., with sections of scribe marks.

A Dougls fir stump, 10 ins. diam., bears S. 15° E.,
 8 lks. dist., with no marks remaining.

add additional accessories

An iron post, 30 ins. long, 2½ ins. diam., set 24 ins. in the ground, for a reference monument, bears North, 10 lks. dist.