

County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey, Subdivisional Lines, T. 30 S. R. 7 W.

CHAINS

A madrone, 45 ins. diam., bears S. 48° W., 24½ lks. dist., with scribe marks 22 S W visible on partially healed blaze. (Record, 23 lks.)

A cedar, 30 ins. diam., bears N. 18° W., 68 lks. dist., has been remarked T30S R7W S15 CS BT on double blaze. (Record, N. 28° W., 67 lks.)

and County Surveyor's bearing trees

A fir, 13 ins. diam., bears N. 26° E., 43 lks. dist., with scribe marks T30S R7W S14 CS BT visible on double blaze.

A fir, 12 ins. diam., bears S. 65° E., 39 lks. dist., with illegible scribe marks visible on partially healed double blaze.

A fir, 6 ins. diam., bears S. 48° W., 8½ lks. dist., with scribe marks S22 CS BT visible on partially healed double blaze.

Add marks ELM 1965 to brass cap.

N. 0° 05' W., bet. secs. 14 and 15, marking and blazing the true line.

Ascend 235 ft. over brokwn SE. slope, through heavy timber and dense undergrowth.

13.70 Spur, slopes E.; desc. 340 ft. over NE. slope.

29.55 Little Doe Creek, 1 lk. wide, course S. 50° E.; asc. 210 ft. over SW. slope.

38.85 The ¼ sec. cor. of secs. 14 and 15, perpetuated by the Douglas County Surveyor in 1964, monumented with an iron post, 1 in. diam., firmly set, extending 12 ins. above the ground, with brass cap mkd.

COUNTY SURVEYORS OFFICE
T 30 S

¼ S 15 | S 14
R 7 W
1964

from which the original bearing trees

A cedar snag, 42 ins. diam., bears S. 82° E., 52½ lks. dist., with scribe marks ¼ S BT visible on partially healed double blaze. (Record, N. 80° E., 50 lks.)

A fir, snag, 50 ins. diam., bears N. 34° W., 28½ lks. dist., with healed double blaze. (Record, a pine, N. 43° W., 25 lks.)

and County Surveyor's bearing trees

A cedar, 10 ins. diam., bears S. 48° E., 18 lks. dist., with scribe marks ¼ S14 CS BT visible on double blaze.

A cedar, 10 ins. diam., bears N. 78° W., 18 lks. dist., with scribe marks ¼ S15 CS BT visible on double blaze.