

County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey, Subdivisional Lines. T. 30 S., R. 7 W.

CHAINS

Add marks BLM 1965 to brass cap.

N. 3° 48' E., beginning new measurement.

Ascend 65 ft. over broken SW. slope.

5.00 Ravine, drains SW.; asc. 270 ft. over broken SW. slope.

20.80 Ridge, bears N. 70° W. and S. 70° E.; also jeep trail, 10 lks. wide, bears same; desc. 265 ft. over broken NE. slope.

40.78 The cor. of secs. 10, 11, 14 and 15, perpetuated by the Douglas County Surveyor in 1964, monumented with an iron post, 1 in. diam., firmly set, extending 12 ins. above the ground, with brass cap mkd.

COUNTY SURVEYORS OFFICE

T 30 S	
S 10	S 11
S 15	S 14
R 7 W	
1964	

from which the original bearing trees

A madrone snag, 10 ins. diam., bears N. 44½° E., 37 lks. dist., with rotted blaze.
(Record, N. 40° E., 33 lks.)

A down madrone, 15 ins. diam., bears S. 10° E., 16 lks. dist., with scribe marks S 7 W visible on rotted blaze.

A madrone, 14 ins. diam., bears S. 66° W., 56 lks. dist., remarked T30S R7W S15 CS BT on double blaze, by County Surveyor. (Record, S. 60° W.)

A fir, 48 ins. diam., bears N. 65° W., 29 lks. dist., with partially opened blaze.
(Record, a madrone, 33 lks.)

and County Surveyor's bearing trees

A white fir, 6 ins. diam., bears N. 45° E., 16 lks. dist., marked T30S R7W S11 CS BT on double blaze.

A white fir, 8 ins. diam., bears N. 27° W., 41 lks. dist., marked T30S R7W S10 CS BT on double blaze.

and bearing trees of which I have no record

A cedar, 40 ins. diam., bears N. 15° E., 56½ lks. dist., marked S11 T30S R7W BT on bark blaze.

A fir, 9 ins. diam., bears S. 35° E., 14 lks. dist., with fragmentary scribe marks visible on partially healed double blaze.

Add marks BLM 1965 to brass cap

Land, mountainous.

Soil, rocky clay loam.

Timber, fir, cedar, madrone, pine, yew chinquapin, live oak, oak, and hemlock; undergrowth, vine maple, hazel, poison oak, Oregon grape, salal, manzanita, huckleberry, blackberry, fern, and ocean spray.