

County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey, Subdivisional Lines, T. 30 S., R. 7 W.

CHAINS

- 1.30 Buck Creek, 4 lks. wide, course E.; asc. 330 ft. over SE. slope.
- 22.00 Spur, slopes S. 30° E.; desc. 150 ft. over NE. slope.
- 30.20 Ravine, drains NE.; asc. 25 ft. over SE. slope.
- 32.40 Spur, slopes E.; desc. 115 ft. over NE. slope.
- 39.94 Point for the $\frac{1}{2}$ sec. cor. of secs. 21 and 22, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 23 ins. in the ground, with brass cap mkd.

T 30 S R 7 W
 S 21 | S 22
 1965

from which

A fir, 36 ins. diam., bears S. 45° E., 25 lks. dist., marked $\frac{1}{4}$ S22 BT.

A fir, 33 ins. diam., bears sS.58° W., 77 lks. dist., mkd. $\frac{1}{4}$ S21 BT.

Descend 2 ft. over NE. slope.

- 40.05 Creek, 2 lks. wide, course SE.; asc. 260 ft. over broken S. slope.
- 59.60 Spur, slopes SE.; desc. 145 ft. over NE. slope.
- 69.65 Creek, 3 lks. wide, course S. 30° E.; asc. 30 ft. over SW. slope.
- 73.208 Creek, 1 lk. wide, course S. 30° W.; asc. 95 ft. over SW. slope.
- 79.88 The cor. of secs. 15, 16, 21 and 22, determined at record bearing and distance from the remaining original bearing trees:

A white fir, 35 ins. diam., bears N. 5° E., 26 lks. dist., with fragmentary scribe marks visible in negative on section of overgrowth.

A down and rotted white fir, 30 ins. diam., bears S. 38° W., 40 lks. dist., no marks remaining.

At the corner point

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.

T 30 S R 7 W
 S 16 | S 15
 S 21 | S 22
 1965

from which new bearing trees