

County Surveyor's Record, Douglas County, Oregon

12874

Some S 6 1/2 W 1/2

T. 23 S., R. 8 W.

CHAINS

The following field notes describe the remonumentation of certain original corner points in township 23 south, range 8 west, of the Willamette Meridian, Oregon, as provided for in the General Special Instructions, Group No. 350, Oregon, dated May 3, 1957, "Investigation of Collateral or Physical Evidence of Corner Positions and Accessories, Followed by Remonumentation of Corner Points, With New Accessories When Needed".

The remonumentations were made at the request of the Coos Bay District Manager for administrative purposes of the Bureau of Land Management.

Remonumentation of Certain Original Corner Points,
T. 23 S., R. 8 W., Willamette Meridian, Oregon

South Boundary

(Remonumenting the corners established by William R. Whipple, in 1894)

The cor. of secs. 32 and 33 only, S. bdy. of the Twp., monumented with an aluminum pipe, 1/2 in. diam., firmly set, protruding 10 ins. above ground, from which the original bearing trees:

A down hemlock, 16 ins. diam., bears N. 7 1/2° E., 38 lks. dist., with healed blaze.

A sawed hemlock stump, 28 ins. diam., bears S. 73 1/2° W., 50 lks. dist., with healed blaze. (Record bearing, S. 75° W.)

A fir, 8 ins. diam., bears N. 68° W., 35 lks. dist., with scribe marks 23S R8W visible on opened blaze. (Record bearing, N. 65° W.)

At the corner point

Set an ironpost, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

T 23 S R 8 W
S 32 | S 33
S 4
T 24 S
1963

from which a new bearing tree

A hemlock, 45 ins. diam., bears N. 82° E., 52 lks. dist., mkd. T23S R8W S33 BT.

Reset the aluminum pipe alongside the iron post.

The 1/4 sec. cor. of sec. 32 only, monumented with an aluminum pipe, 1/2 in. diam., firmly set, protruding 8 ins. above ground, from which the original bearing trees:

A down hemlock, 60 ins. diam., bears N. 29° W., 17 lks. dist., with a healed blaze.