

County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey, Subdivisional Lines, T. 29 S., R. 4 W.

CHAINS

A A cedar, 40 ins. diam., bears S. $42\frac{1}{4}^\circ$ E., 57 lks. dist., with a healed blaze.

A stump hole, bears S. $71\frac{1}{2}^\circ$ W., 36 lks. dist.

A fir snag, 23 ins. diam., bears N. $8\frac{1}{2}^\circ$ W., 34 lks. dist., with a healed blaze.

and bearing trees mkd. by Byron in 1962

A fir, 13 ins. diam., bears N. $\frac{1}{2}^\circ$ E., 65 lks. dist., mkd. T29S R4W S12 CS BT on double blaze.

A cedar, 13 ins. diam., bears N. $34\frac{1}{2}^\circ$ W., 55 lks. dist., mkd. T29S R4W S11 CS BT on double blaze.

At the corner point

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.

T 29 S R 4 W
 $\frac{S\ 11}{S\ 14} | \frac{S\ 12}{S\ 13}$
 1964

FD. ok by
 W. PUPPET
 6/83
 M 97-61

from which a new bearing tree

A fir, 7 ins. diam. bears S. 53° E., 86 lks. dist., mkd. T29S R4W S13 BT.

Reset iron pipe alongside iron post.

Corner is in SW. corner of logged area.

S. $87^\circ 48'$ E., bet. secs. 12 and 13, marking and blazing the true line.

Ascend 100 ft. along N. slope and S. edge of logged area, through dense undergrowth.

6.70 Top of ascent, slopes N.; desc. 105 ft. over NE. slope.

13.15 Creek, 1 lk. wide, course N.; asc. 325 ft. over NW. slope.

30.35 Ridge, bears N. 25° E. and S. 25° W.; desc. 165 ft. over SE. slope.

37.03 Point for the $\frac{1}{4}$ sec. cor. of secs. 12 and 13, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins. in the ground, with brass cap mkd.

T 29 S R 4 W
 $\frac{1}{4} \frac{S\ 12}{S\ 13}$
 1964

from which

A fir, 38 ins. diam., bears North, 66 lks. dist., mkd. $\frac{1}{4}$ S12 BT.

A fir, 17 ins. diam., bears S. $8\frac{1}{2}^\circ$ W., 20 lks. dist., mkd. $\frac{1}{4}$ S13 BT.

Descend 100 ft. over SE. slope.