

## County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey, Portion of S. Bdy., T. 29 S., R. 8 W.

CHAINS

and bearing trees marked by Byron

A hemlock, 16 ins. diam., bears S.  $60^{\circ}$  W.,  $58\frac{1}{2}$  lks.  
dist., mkd. T30S R8W S6 CS BT on a double blaze.

A hemlock, 12 ins. diam., bears N.  $3\frac{1}{4}^{\circ}$  W., 120 lks.  
dist., mkd. T29S R8W S31 CS BT on a double blaze.

At the corner point

Set an iron post, 28 ins. long,  $2\frac{1}{2}$  ins. diam., 22 ins. in  
the ground, with brass cap mkd.

$$\begin{array}{r} T\ 29\ S\ R\ 8\ W \\ \quad S\ 31\ | \ S\ 32 \\ \hline T\ 30\ S\ R\ 8\ W \\ \quad S\ 6 \\ 1965 \end{array}$$

Reset the iron rod alongside the iron post.

From this point, the cor. of secs. 5 and 6 only, on the  
N. bdy. of T. 30 S., R. 8 W., bears S.  $88^{\circ} 07'$  E., 0.76 chs.  
dist., perpetuated and recorded by James W. Byron, Deputy  
County Surveyor, in 1958, monumented with an iron post,  
 $1\frac{1}{2}$  ins. diam., firmly set, extending 8 ins. above ground,  
with brass cap mkd.

## COUNTY SURVEYORS OFFICE

$$\begin{array}{r} R \\ 8 \\ W \\ \quad T\ 29\ S \\ \quad \quad S\ 32 \\ \quad \quad \hline \quad \quad S\ 6\ | \ S\ 5 \\ \quad \quad \quad CC \\ \quad \quad \quad 1958 \end{array}$$

from which the remaining original bearing trees:

A down hemlock, 26 ins. diam., bears N.  $21^{\circ}$  E., 32 lks.  
dist., mkd. T29S R8W S32 on an opened blaze.

A fir, 46 ins. diam., bears S.  $30^{\circ}$  W., 40 lks. dist.,  
38 lks. to face, mkd. T30S R8W S6 BT on a bark  
blaze. (Record, 38 lks.)

and bearing trees marked by Byron

A down hemlock, 8 ins. diam., bears S.  $25^{\circ}$  E., 47 lks.  
dist., mkd. T30S R8W CC S5 CS on partially  
healed double. blaze.

A cedar, 5 ins. diam., bears S.  $10\frac{1}{2}^{\circ}$  W., 66 lks.  
dist., mkd. S 6 CS BT on an open blaze.

At the corner point

Set an iron post, 28 ins. long,  $2\frac{1}{2}$  ins. diam., 24 ins. in  
the ground, with brass cap mkd.

$$\begin{array}{r} T\ 29\ S\ R\ 8\ W \\ \quad S\ 32 \\ \quad \quad \hline \quad \quad S\ 6\ | \ S\ 5 \\ \quad \quad \quad CC \\ \quad \quad \quad 1965 \end{array}$$

from which a new bearing tree

A fir, 20 ins. diam., bears S.  $64\frac{1}{2}^{\circ}$  E., 66 lks.  
dist., mkd. T30S R8W S5 BT.

Reset the county iron post inverted alongside the  
iron post.