

County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey, Portion of S. Bdy., T. 29 S., R. 8 W.

CHAINS

- 28.40 Spur, slopes N.; desc. 95 ft. over broken NW. slope.
- 29.80 Dirt road, 20 lks. wide, bears N. 20° W. and S. 20° E.
- 39.65 Creek, 3 lks. wide, course North; asc. 90 ft. over NE. slope.
- 43.77 The cor. of Tps. 29 and 30 S., Rs. 8 and 9 W., perpetuated and recorded by James W. Bryon, Deputy County Surveyor, in 1958, the corner point is occupied by the original corner tree, a sugar pine, 45 ins. diam., mkd. with healed blazes on the NE. and SE. sides, from which the remains of the original bearing trees:

A sugar pine, 45 ins. diam., bears N. 80° E., 5 lks. dist., no original marks remaining. Remarkd T30S R8W WC S6 CS BT on a double blaze by Byron.

A fir, 27 ins. diam., bears S. 88° W., 28 lks. dist., mkd. W S36 on an open blaze.

A sawed fir stump, 36 ins. diam., bears N. 50° W., 73 lks. dist., with no marks remaining.

and bearing trees and iron post marked by Byron

A fir, 21 ins. diam., bears N. 57° E., 58 lks. dist., mkd. with a healed double blaze.

A fir, 18 ins. diam., bears S. 66° W., 34 lks. dist., mkd. with a partially healed double blaze.

A fir, 27 ins. diam., bears N. 49½° W., 59 lks. dist., mkd. with a partially healed double blaze.

An iron post, 1½ ins. diam., firmly set, 16 ins. above the ground, with brass cap mkd. COUNTY SURVEYORS OFFICE T29S WC T30S R9W R8W S1 S6 S31 S36 Cor. 10 FT S 1958, bears North, 15 lks. dist.

Add a reference monument

An iron post, 28 ins. long, 2½ ins. diam., set 22 ins. in the ground, for a reference monument, bears S. 35° E., 18½ lks. dist., with brass cap mkd. RM T30S R8W S6 1965 and an arrow pointing to the corner.

Land, rolling hills

Soil, rocky clay.

Timber, fir, pine, cedar, hemlock, maple, madrone, oak, dogwood, yew, chinquapin, and alder; undergrowth, salal, poison oak, manzanita, hazel, arrowwood, Oregon grape, huckleberry, willow, vine maple, vines and ferns.

Dependent Resurvey of a Portion of the W. Bdy.,
T. 29 S., R. 8 W., Willamette Meridian, Oregon

(Restoring the 1856 survey by Dennis Hathorn.)

From the cor. of Tps. 29 and 30 S., Rs. 8 and 9 W.

N. 0° 22' W., bet. secs. 31 and 36.

Descend 205 ft. over NE. slope, along E. edge of logged area, through dense through dense undergrowth.