

## County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey, Portion of W. Bdy., T. 29 S., R. 8 W.

## CHAINS

- 22.75 Dirt road, 15 lks. wide, bears N. 15° E., and S. 15° W.
- 25.60 Same road, bears N. 25° W. and S. 25° E.
- 30.30 Same road, bears N. 20° E. and S. 20° W.
- 40.50 The  $\frac{1}{4}$  sec. cor. of secs. 31 and 36, perpetuated and recorded by James W. Byron, Deputy County Surveyor, in 1958, monumented with an iron post,  $1\frac{1}{2}$  ins. diam., firmly set, extending 14 ins. above ground, with brass cap mkd.

## COUNTY SURVEYORS OFFICE

	T 29 S		
$\frac{1}{4}$	S	S	R
R 36	31	8	
9			W
W	1958		

from which the remains of the original bearing trees:

A sawed fir stump, 27 ins. diam., bears S. 33° E., 33 lks. dist., mkd. BT on an opened blaze and remarked  $\frac{1}{4}$  S BT on a bark blaze.

A sawed fir stump, 52 ins. diam., bears N. 42° W., 9 lks. dist.; mkd.  $\frac{1}{4}$  CS on a bark blaze.

and bearing trees marked by Byron

A fir, 15 ins. diam., bears N. 9° E., 48 lks. dist., mkd. with a partially healed double blaze.

A fir, 10 ins. diam., bears S. 26 $\frac{1}{2}$ ° W., 20 lks. dist., mkd. with a partially healed double blaze.

Add the marks BLM 1965 to top of brass cap.

N. 0° 02' W., beginning new measurement.

Descend 115 ft. over NE. slope, along E. edge of logged area, through dense undergrowth.

- 20.29 Point for the N 1/16 sec. cor. of secs. 31 and 36.

Set an iron post, 28 ins. long,  $2\frac{1}{2}$  ins. diam., 24 ins. in the ground, with brass cap mkd.

	N 1/16	
S 36	S	31
	1965	

from which

A fir, 20 ins. diam., bears N. 53° E., 64 lks. dist., mkd. N. 1/16 S31 BT.

A fir, 18 ins. diam., bears N. 59° W., 22 lks. dist., mkd. N 1/16 S36 BT.

Descend 15 ft. over NE. slope.

- 21.50 Creek, 5 lks. wide, course N. 40° W.; asc. 30 ft. over SW. slope.

- 22.70 Dirt road, 15 lks. wide, bears E. and W.