

## County Surveyor's Record, Douglas County, Oregon

## CHAINS

Dependent Resurvey, Portion of the Subdivisional Lines,  
T. 29 S., R. 8 W., Willamette Meridian, Oregon

(Restoring the 1856 survey by Dennis Hathorn.)

From the cor. of secs. 31 and 32, only, on the S. Bdy.  
of the Tp., previously described.

N. 0° 17' E., bet. secs. 31 and 32.

Descend 110 ft. over NE. slope, through logged area.

- 1.55 Dirt road, 20 lks. wide, bears N. 50° W. and S. 50° E.
- 5.45 Day Creek, 2 lks. wide, course N. 50° W.; asc. 175 ft.  
over SW. slope.
- 14.25 Dirt road, 25 lks. wide, bears N. 30° W. and S. 30° E.
- 16.85 Gravelled road, 25 lks. wide, bears S. 60° E. and N. 35° W.
- 18.15 Spur, slopes N. 40° W.; desc. 160 ft. over NE. slope,  
changing to NW. slope.
- 21.40 Gravelled road, 25 lks. wide, bears N. 10° W. and S. 35° W.  
on a curve.
- 35.70 Dirt road, 15 lks. wide, bears E. and W.
- 40.30 The  $\frac{1}{4}$  sec. cor. of secs. 31 and 32, perpetuated and  
recorded by James W. Byron, Deputy County Surveyor,  
in 1958, monumented with an iron post,  $1\frac{1}{2}$  ins. diam.,  
firmly set, extending 14 ins. above ground, with  
brass cap mkd.

## COUNTY SURVEYORS OFFICE

	S	S
$\frac{1}{4}$		
	31	32
	T 29 S R 8 W	
	1958	

from which the remains of the original SE. bearing tree:

A stump hole, bears S. 22° E., 15 lks. dist.

and bearing trees marked by Byron

A fir, 15 ins. diam., bears N. 19° E., 19 lks.  
dist., with scribe marks visible on partially  
healed double blaze.

A cedar, 19 ins. diam., bears N. 55 $\frac{1}{2}$ ° W., 62 lks.  
dist., mkd.  $\frac{1}{4}$  S31 CS BT on a double blaze.

Add the marks ELM 1965 to top of brass cap.

N. 0° 04' E., beginning new measurement.

Descend 195 ft. over NW. slope, through logged area.

- 12.60 Dirt road, 15 lks. wide, bears E. and W.
- 31.00 Creek, 3 lks. wide, course N. 80° W.; asc. 15 ft. over  
S. slope.
- 32.30 Top of ascent, slopes W.; desc. 5 ft. over NW. slope.