

## County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey, Portion Subdivisional Lines, T. 23 S., R. 7 W.

CHAINS

A white oak, 30 ins. diam., bears N. 79° E., 171 lks. dist., with fragmentary scribe marks visible on partially healed blaze.

S. 89° 58' W., beginning new measurement.

Descend 10 ft. over SW. slope.

2.25 Creek, 1 lk. wide, course S. 25° W.; asc. 140 ft. over SE. slope.

10.50 Oregon State Highway No. 225, blacktop surface, 30 lks. wide, bears N. 55° E. and S. 55° W.

13.70 Spur, slopes S. 5° E.; desc. 35 ft. over SW. slope.

15.75 Ravine, drains S. 10° E.; asc. 100 ft. over E. slope.

20.19 Point for the W 1/16 sec. cor. of secs. 17 and 20.

Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap marked

W 1/16  $\frac{S 17}{S 20}$   
1965

from which

A fir, 19 ins. diam., bears N. 73° W., 16½ lks. dist., mkd. W 1/16 S17 BT.

A fir, 14 ins. diam., bears S. 30° W., 12 lks. dist., mkd. W 1/16 S20 BT.

Ascend 120 ft. over general E. slope.

25.00 Spur, slopes SE.; desc. 160 ft. over SW. slope.

29.60 Ravine, drains S. 5° E.; asc. 235 ft. over E. slope.

40.38 The cor. of secs. 17, 18, 19, and 20, remonumented by J. W. Byron, Deputy County Surveyor, in 1960, with an iron post, 1 in. diam., firmly set, projecting 14 ins. above ground, with brass cap marked

COUNTY SURVEYORS OFFICE

T 23 S R 7 W

$\frac{S 18 S 17}{S 19 S 20}$

1960

from which an original bearing tree

A sawed fir stump, 36 ins. diam., bears S. 27° W., 29 lks. dist., with scribe marks 23S W S19 visible on opened blaze.

and bearing trees marked by Byron

A maple, 17 ins. diam., bears N. 44° E., 37½ lks. dist., with scribe marks T23S R7W S17 CS BT.

A fir, snag, 17 ins. diam., bears S. 20° E., 57 lks. dist., with fragmentary scribe marks visible on pitched over double blaze.