

County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey, Portion Subdivisional Lines, T. 23 S., R. 7 W.

CHAINS	<p>Land, mountainous. Soil, sandy clay loam. Timber, fir, hemlock, cedar, maple, alder, myrtle, chinquapin, and madrone; undergrowth, vine maple, salmon-berry, huckleberry, hazel, arrowwood, poison oak, salal, Oregon grape, Scotchbroom, ceanothus, blackberry, and fern.</p>
	<p>Subdivision of Section 17, T. 23 S., R. 7 W. Willamette Meridian, Oregon</p>
	<p>From the $\frac{1}{4}$ sec. cor. of secs. 17 and 20. N. $0^{\circ} 23'$ E., on the N. and S. center line of sec. 17. Descend 5 ft. along W. slope, through scattering timber and dense undergrowth.</p> <p>3.40 Ravine, drains S. 35° W.; asc. 210 ft. over general S. slope.</p> <p>10.75 Graveled road, 15 lks. wide, bears N. 35° W. and S. 35° E.</p> <p>11.60 Dirt road, 15 lks. wide, bears N. 40° E. and S. 40° W.</p> <p>15.00 Spur, slopes S. 40° W.; desc. 45 ft. over NW. slope.</p> <p>19.66 Point for the center S $\frac{1}{16}$ sec. cor. of sec. 17.</p>
	<p>At the corner point, which falls in a graveled road, 20 lks. wide, in curve, bearing N. 10° W. and S. 10° W., set a steel bar, 18 ins. long, $\frac{1}{2} \times \frac{3}{4}$ in. in cross section, 6 ins. below surface of road, from which</p> <p>A fir, 20 ins. diam., bears S. 43° E., 46 lks. dist., mkd. C S$\frac{1}{16}$ S17 BT.</p> <p>A fir, 14 ins. diam., bears N. 15° W., 164 lks. dist., mkd. C S$\frac{1}{16}$ S17 BT.</p> <p>An iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., set 20 ins. in the ground, for a reference monument, bears East, 50 lks. dist., with brass cap marked, C S$\frac{1}{16}$ S17 RM 1965 and an arrow pointing to the corner.</p>
	<p>Corner falls at bottom of descent, slopes W.; asc. 75 ft. over broken general S. slope.</p>
	<p>23.75 Enter prune orchard, edge bears N. 55° W. and S. 55° E.</p>
	<p>27.50 Dirt road, 15 lks. wide, bears N. 50° E. and S. 50° W.; also enter pasture land, edge bears same as road.</p>
	<p>39.32 Point for the center $\frac{1}{4}$ sec. cor. of sec. 17 at the intersection with the E. and W. center line.</p> <p>Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins. in the ground, with brass cap marked</p>
	<p style="text-align: center;">C $\frac{1}{4}$ S 17 1965</p>
	<p>from which</p> <p>A fir, 16 ins. diam., bears N. $20\frac{1}{2}^{\circ}$ W., 160 lks. dist., mkd. C$\frac{1}{4}$ S17 BT.</p>