

County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey, Portion of W. Bdy., T. 30 S., R. 3 W.

CHAINS

Beginning at the former cor. of secs. 7, 12, 13 and 18, on the W. bdy. of the Tp., established by Nathaniel Ford in 1854, which became an angle point in 1893 when William Bushey established the closing cor. of secs. 7 and 18, determined at record bearing and distance from the remaining original bearing trees:

The rotted remains of a fir stump, size indeterminate bears N. 15° E., 17 lks. dist.

The rotted remains of a fir stump, size indeterminate, bears S. 50° E., 14 lks. dist.

A sawed fir stump, 32 ins. diam., bears N. 88° W., 34 lks. dist., mkd. BT on partly opened blaze.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

```

      T 30 S T 30 S
        AP
      S 12 | S 18
      R 4 W | R 3 W
          1965
  
```

from which new bearing trees

A fir, 6 ins. diam., bears S. 17° E., 13 lks. dist., mkd. AP S18 BT.

A fir, 6 ins. diam., bears S. 38° W., 21½ lks. dist., mkd. AP S12 BT.

N. 2° 17' E., bet. secs. 12 and 18, on the W. bdy. of the Tp., marking and blazing the true line.

Descend 235 ft. over NE. slope, across logged area, through scattering timber and dense undergrowth.

8.85 True point for the closing cor. of secs. 7 and 18, T. 30 S., R. 3 W., hereinafter described.

Thence on the W. bdy. of section 7.

Descend 285 ft. over NE. slope.

31.80 Bottom of descent, slopes NW.; asc. 15 ft. over S. slope, along the top of spur.

37.29 Point for the former ¼ sec. cor. of secs. 7 and 12, established by Nathaniel Ford in 1854, which is now an angle point, restored by the method of irregular boundaries, based on the Bushey retracement; there is no remaining evidence of the original corner.

Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.

```

      T 30 S T 30 S
        AP
      S 12 | S 7
      R 4 W | R 3 W
          1965
  
```

from which