

County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey, Portion of W. Bdy., T. 30 S., R. 3 W.

CHAINS	
	<p>A cedar, 8 ins. diam., bears N. $30\frac{1}{2}^{\circ}$ E., $70\frac{1}{2}$ lks. dist., mkd. AP S7 BT.</p> <p>A fir, 10 ins. diam., bears S. 87° W., 153 lks. dist., mkd. AP S12 BT.</p> <p>The angle point is located on a spur, slopes N. 15° W.</p> <p>From this point, a point established by Robert M. Thompson, Registered Engineer, in 1956, bears S. $0^{\circ} 27'$ E., 3.10 chs. dist., monumented with an iron pipe, 1 in. diam., firmly set, extending 6 ins. above ground, from which bearing trees marked by Thompson:</p> <p>A sawed madrone stump, 14 ins. diam., bears N. $22\frac{1}{2}^{\circ}$ E., 83 lks. dist., mkd. BT on opened blaze.</p> <p>A fir snag, 8 ins. diam., bears N. $49\frac{1}{2}^{\circ}$ W., 191 lks. dist., mkd. 3683 BT on open double blaze.</p>
	<p>N. $2^{\circ} 34'$ E., beginning new measurement.</p> <p>Descend 30 ft. over NE. slope, changing to N. slope.</p>
12.01	<p>Point for the $\frac{1}{4}$ sec. cor. of sec. 7 only, hereinafter described.</p> <p>Descend 345 ft. over N. slope.</p>
15.80	<p>Gravelled road, 20 lks. wide, bears N. 75° W. and S. 75° E.</p>
18.60	<p>Same road, bears N. 80° W. and N. 70° E.</p>
20.62	<p>From this point the closing corner of secs. 1 and 12, T. 30 S., R. 4 W., bears West, 0.085 chs. dist., monumented with an iron pipe, $\frac{3}{4}$ in. diam., firmly set, extending 4 ins. above ground, from which the original bearing trees:</p> <p>A fir, 20 ins. diam., bears S. 80° W., 17 lks. dist., with healed blaze.</p> <p>A fir, 29 ins. diam., bears N. 29° W., 21 lks. dist., with scribe mark W visible on partly opened blaze on SE. face, and with scribe marks T30S visible on opened blaze on NE face. The NE face of this tree was marked by William H. Byars in 1872. Briggs reported a Byars corner 25 lks. North of the closing corner of secs. 1 and 12, but did not describe it, and there is no other record of a Byars survey. I destroy the marks on the NE. face.</p> <p>From the closing cor. , a point established by Ben B. Irving, Deputy County Surveyor, in 1928, bears N. 30° E., 0.22 chs. dist., monumented with a basalt stone, 14 x 8 x 6 ins., firmly set, extending 4 ins. above ground, from which a bearing tree marked by Byars in 1872:</p> <p>A fir, 18 ins. diam., bears N. 29° W., 17 lks. dist., mkd. S T30 R 4 W on opened blaze. I destroy the marks on this tree.</p> <p>Descend 140 ft. over N. slope.</p>
27.25	<p>Days Creek, 10 lks. wide, course N. 18° W.; asc. 15 ft. over gradual S. slope.</p>