

Dependent Resurvey, Portion of W. Bdy., T. 30 S., R. 3 W.

CHAINS
33.45

The cor. of secs. 6 and 7 only, perpetuated and recorded by Ben B. Irving, County Surveyor, in 1953, monumented with an iron post, 1 in. diam., firmly set, extending 10 ins. above the ground, with brass cap mkd.

*Find OK 10/92
R. Brown M 112-62*

COUNTY SURVEYORS

R	T	30	S	R
		6		
4	1	7		3
W		1953		W

 OFFICE

from which the remaining original bearing trees

A sawed fir stump, 36 ins. diam., bears N. 88° E., 33 lks. dist., mkd. 7 BT. on a bark blaze. (Record, 30 lks.)

A maple, 25 ins. diam., bears S. 19° E., 38 lks. dist., with illegible scribe marks on partly healed blaze.

A white fir snag, 25 ins. diam., bears S. 18° W., 33 lks. dist., with healed blaze. (Record, 32 lks.)

and bearing trees marked by Irving.

A sawed oak stump, 14 ins. diam., bears N. 79° E., 312 lks. dist., with healed blaze.

A fir, 24 ins. diam., bears S. 50° W., 48 lks. dist., with healed blaze.

and a new bearing tree

A fir, 12 ins. diam., bears N. 61° E., 148 lks. dist., mkd. T30S R3W S6 BT.

Add the marks BLM 1965 to the brass cap.

Land, mountainous.

Soil, rocky clay loam.

Timber, fir, cedar, oak, alder, yew, madrone, chinquapin, and maple; undergrowth, vine maple, willow, poison oak, salal, oceanspray, salmonberry, huckleberry, blackberry, fern and hazel.

Dependent Resurvey of a Portion of the Subdivisional Lines, T. 30 S., R. 3 W., Willamette Meridian, Oregon. (Restoring the 1857 survey by Dennis Hathorn, and the 1893 survey by William M. Bushey.)

From the cor. of secs. 7, 8, 17 and 18, monumentd with the original basalt stone, 12 x 12 x 10 ins., firmly set 8 ins. in the ground, marked with 5 grooves on E., and 4 grooves on S. face, from which the remaining original bearing trees:

A fir, 34 ins. diam., bears S. 33½° E., 42 lks. dist., with partly healed and burned blaze.

The stump hole of a maple, bears S. 27½° W., 69 lks. dist., (Record, 66½ lks.)