County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey, Subdivisional Lines, T. 30 S., R. 3 W.

CHAINS

A fir snag, 9 ins. diam., bears N. 36½° E., 14 lks. dist., mkd. BT on opened blaze.

A fir, 46 ins. diam., bears S. 75° E., 33 lks. dist., with healed blaze. (Record, 35 lks.)

and a bearing tree marked by Thompson

A fir, 15ins. diam., bears N. 41½° W., 37 lks. dist., with healed double blaze.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground, with brass cap mkd.

T 30 S R 3 W
¼ S 7
S 18
1965

Referenced out for logging 3/5/81 - Doug Co Surveyor off. L. Monreau see C.S. 59/30

Deposit the original stone and the iron pipe alongside the iron post.

From this point a United States Geological Survey Bench Mark, bears S. 49° 32' W., 41.53 chs. dist., monumented with a brass cap, 3½ ins. diam., firmly seated in the top of a boulder, 8 ins. above ground, mkd. BLAND MTN. 1953. The bench mark is under Bland Mountain Lookout Tower.

S. 85° 19' W., beginning new measurement.

Descend 575 ft. over W. slope, along N. edge of logged area, through heavy timber and dense undergrowth.

13.70 Creek, 1 lk. wide, course N.; leave timber, edge bears generally N. and E., enter logged area with scattering timber and dense undergrowth; asc. 65 ft. over NE. slope.

15.60 Spur, slopes N. 10° E.; desc. 15 ft. over NW. slope.

17.20 Ravine, drains N. 10° E.; asc. 115 ft. over NE. slope.

19.93 Point for the W 1/16 sec. cor. of secs. 7 and 18.

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

W 1/16 S 7
S 18
1965

from which

A fir, 16 ins. diam., bears N. 12¼° W., 88 lks. dist., mkd. W1/16 S7 BT.

A fir, 11 ins. diam., bears S. 10½° E., 60 lks. dist., mkd. W1/16 S18 BT.

Ascend 195 ft. over NE. slope.

25.50 Spur, slopes N. 10° E.; desc. 185 ft. over NW. slope.

34.10 Ravine, drains N. 30° E.; asc. 170 ft. over NE. slope.