

County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey, Subdivisional Lines, T. 30 S., R. 3 W.

CHAINS

37.10 Gravelled road, 20 lks. wide, bears N. and S.

37.61 Intersect the W. bdy of the Tp.

True point for the closing cor. of secs. 7 and 18.

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.

T	30	S	T	30	S
	S	12	$\frac{S}{S}$	7	CC
				18	
R	4	W	R	3	W
				1965	

from which

A fir, 16 ins. diam., bears N. $62\frac{1}{2}^{\circ}$ E., 120 lks. dist., mkd. T30S R3W S7 CC BT.A fir, 18 ins. diam., bears S. $44\frac{1}{2}^{\circ}$ E., 209 lks. dist., mkd. T30S R3W S18 CC BT.

From this point the original closing cor. of secs. 7 and 18, bears S. $85^{\circ} 19' W.$, 0.55 chs. dist., perpetuated and recorded by Robert Thompson, Registered Engineer, in 1956, monumented with an iron pipe, 1 in. diam., firmly set, extending 3 ins. above ground, from which the original bearing trees:

A sawed fir stump, 38 ins. diam., bears N. $23 \frac{3}{4}^{\circ}$ E., 14 lks. dist., mkd. T30S R3 S on opened blaze.A fir snag, 22 ins. diam., bears S. $43\frac{1}{2}^{\circ}$ E., 17 lks. dist., with opened and burned blaze.A rotted fir stump, 14 ins. diam., bears N. $53^{\circ} W.$, $45 \frac{3}{4}$ lks. dist., mkd. 30 R3W 7 on section of blaze lying beside stump. (Record, N. $51^{\circ} W.$)

and bearing trees marked by Thompson

A cedar, 12 ins. diam., bears N. $56\frac{1}{2}^{\circ}$ E., 66 lks. dist., mkd. T30S R3W S7 BT on partly healed double blaze.A fir, 19 ins. diam., bears N. $41^{\circ} W.$, 121 lks. dist., mkd. 30 R3W BT on partly healed double blaze.From this same point, the angle point bet. secs. 12 and 18 bears S. $2^{\circ} 17' W.$, 8.85 chs. dist.

Land, mountainous.

Soil, rocky clay loam.

Timber, fir, cedar, oak, alder, yew, madrone, chinquapin, and maple; undergrowth, vine maple, willow, poison oak, salal, oceanspray, salmonberry, huckleberry, blackberry, fern and hazel.

From the cor. of secs. 5 and 6 only, on the N. bdy. of sec. 8, perpetuated and recorded by John H. Merckham, Registered Engineer, in 1951, monumented with an iron pipe, 1 in. diam., firmly set, extending 12 ins. above ground, subsequently remonumented by James W. Byron, Deputy County Surveyor, in 1963, with an iron post, 1 in. diam., firmly set, extending 16 ins. above ground with brass cap mkd.