

County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey, Subdivisional Lines, T. 30 S., R. 3 W.

CHAINS

COUNTY SURVEYORS

T	30	S	R
S	6	S	5
		8	W
1963			
OFFICE			

FROM which the remainng original bearing trees:

A sawed fir stump, 40 ins. diam., bears N. 86° E., 65 lks. dist., with opened blaze, no marks visible. (Record, N. 80° E.)

A sawed fir stump, 36 ins. diam., bears S. 18° E., 32 lks. dist., mkd. T30S R3W S8 on opened blaze. (Record, S. 40° E.) The marks were reported destroyed by Bushey in 1893.

A maple, 15 ins. diam., bears N. 60° W., 28 lks. dist., with illegible scribe marks on opened blaze.

And a bearing tree marked by Markham

A maple, 15 ins. diam., bears S. 46° E., 23 lks. dist., with healed double blaze.

And a bearing tree marked by Byron

A fir, 8 ins. diam., bears N. 49° E., 33 lks. dist., mkd. S5 CS BT on double blaze.

Add the marks HLM 1965 to the brass cap.

N. 89° 58' W., on the S. bdy. of sec. 6.

Descend 15 ft. over NW. slope, across logged area through scattering timber and dense undergrowth.

0.25 Ravine, drains N.; asc. 25 ft. over NE. slope.

2.80 Spur, slopes N.; desc. 60 ft. over NW. slope.

6.16 True point for the closing cor. of secs. 7 and 8, hereinafter described.

descend 240 ft. over NW. slope.

19.90 Foot of hill, bears NE. and SW., enter open pasture land; desc. 10 ft. over gradual N.W. slope.

24.45 Days Creek, 10 lks. wide, course S. 50° W.; asc. 35 ft. over SE. slope.

26.60 County road, asphalt paving, 30 lks. wide, bears N. 70° E. and S. 70° W.

35.00 Top of ascent, slopes S.; desc. 20 ft. over SW. slope.

39.93 From this point, a point established by Ben B. Irving, Deputy County Surveyor, in 1928, bears South, 0.04 chs. dist., monumentd with a flint stone, 20 x 6 x 4 ins., firmly set, extending 2 ins. above ground, subsequently remonumented by James W. Byron, Deputy County Surveyor, in 1963, with an iron post 1 in. diam., firmly set, extending 11 ins. above ground, with brass cap mkd.