

County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey, Subdivisional Lines, T. 30 S., R. 3 W.

CHAINS

*Final OK 10/92
P. Brown M112-62*

COUNTY SURVEYORS
T 30 S
SOUTH R
¼ S 6 3
W
1963
OFFICE

from which bearing trees marked by Irving

A white oak, 7 ins. diam., bears N. 45° E., 8 lks. dist., with healed blaze.

A white oak, 17 ins. diam., bears N. 65° W., 11 lks. dist., with illegible scribe marks on partly healed blaze.

and a bearing tree marked by Byron

A white oak, 11 ins. diam., bears S. 46° E., 8 lks. dist., mkd. ¼ S CS BT on double blaze.

45.44 Point for the ¼ sec. cor. of sec. 7 only, hereinafter described.

Descend 5 ft. over sSW slope.

46.45 Creek, 1 lk. wide, course S. 15° W.; asc. 10 ft. over SE. slope.

47.325 From this point, a point established by Ben B. Irving, Deputy County Surveyor, in 1928, bears North, 0.09 chs. dist., monumented with an iron pipe, 1 in. diam., firmly set, extending 1 in. above ground, from which bearing trees marked by Irving:

A white oak, 23 ins. diam., bears S. 17½° E., 329 lks. dist., with illegible scribe marks on partly healed blaze.

A white oak, 20 ins. diam., bears S. 40 ¾° W., 339 lks. dist., with healed blaze.

53.50 Top of ascent, slopes S.; desc. 20 ft. over SW. slope.

63.50 Bottom of descent, slopes SW.; enter logged area with scattering timber and dense undergrowth, edge bears generally E. and SW.; asc. 65 ft. over SE. slope.

68.80 Spur, slopes S.; desc. 90 ft. over SW. slope.

79.35 County road, asphalt paving, 30 lks. wide, bears N. 50° W. and S. 50° E.

80.88 The cor. of secs. 6 and 7 only, on the W. bdy. of the Twp.

Land, E ½ mile mountainous, W. ¾ mile rolling bottom land. Soil, rocky and sandy clay loam.

Timber, fir, cedar, oak, alder, yew, madrone, chinquapin, and maple; undergrowth, vine maple, willow, poison oak, Salal, oceanspray, salmonberry, huckleberry, blackberry, fern, and hazel.

From the cor. of secs. 7, 8, 17 and 18.

N. 0° 06' W., bet. secs. 7 and 8.