

County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey, Subdivisional Lines, T. 30 S., R. 3 W.

CHAINS

A white oak, 16 ins. diam., bears N. 68° E., 71 lks. dist., with healed double blaze.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.

T 30 S R 3 W  
 ↑  
 S 7 | S 8  
 1965

Deposit the iron pipes alongside the iron post.

N. 0° 55' E., beginning new measurement.

Ascend 200 ft. over SW. slope.

12.00 Spur, slopes SW.; desc. 115 ft. over NW. slope.

16.69 The original closing cor. of secs. 7 and 8, perpetuated and recorded by John H. Markham, Registered Engineer, in 1951, monumented with an iron pipe, 1 in. diam., firmly set, extending 3 ins. above ground, from which the remaining original bearing trees:

A sawed fir stump, 28 ins. diam., bears S. 35½° W., 39 lks. dist., with healed blaze.

A fir, 24 ins. diam., bears N. 7½° W., 28 lks. dist., with headed blaze and scribe marks S6 BT on bark blaze.

and a bearing tree marked by James W. Byron, Deputy County Surveyor, in 1963.

A maple, 8 ins. diam., bears S. 2° W., 21 lks. dist., mkd. CC T30S R3W S7 CS BT on double blaze.

Descend 1 ft. over NW. slope.

16.72 Intersect the S. bdy of sec. 6.

True point for the closing corner of secs. 7 and 8.

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

S 6  
 ———  
 S 7 | S 8  
 CC  
 T 30 S R 3 W  
 1965

from which

A fir, 16 ins. diam., bears S. 10° E., 77 lks. dist., mkd. T30S R3W S8 CC BT.

A fir, 4 ins. diam., bears S. 51° W., 56½ lks. dist., mkd. X BT.

Land, mountainous.

Soil, rocky clay loam.

Timber, fir, cedar oak, alder, yew, madrone, chinquapin, and maple; undergrowth, vine maple, willow, poison oak, salal, oceanspray, salmonberry, huckleberry, blackberry, fern & hazel.