

County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey, Subdivisional Lines, T. 30 S., R. 3 W.

CHAINS

To establish the  $\frac{1}{4}$  sec. cor. of sec. 7 only, on the W. bdy. of the Tp., I return to the angle point bet. secs. 7 and 12, and run

N.  $2^{\circ} 34'$  E., on the W. bdy. of sec. 7.

12.01

Point for the  $\frac{1}{4}$  sec. cor. of sec. 7 only, at proportionate distance in latitude.

Set an iron post, 28 ins. long,  $2\frac{1}{2}$  ins. diam., 22 ins. in the ground, with brass cap mkd.

T 30 S  
 $\frac{1}{4}$  S 7  
 R 3 W  
 1965

from which

A fir, 9 ins. diam., bears N.  $67\frac{1}{2}^{\circ}$  E.,  $27\frac{1}{2}$  lks. dist., mkd.  $\frac{1}{4}$  S7 BT.

A black oak, 13 ins. diam., bears South, 4 lks. dist., mkd.  $\frac{1}{4}$  S7 BT.

From this point, a point established by Robert M. Thompson, Registered Engineer, in 1956, bears S.  $33^{\circ} 26'$  E., 0.82 chs. dist., monumented with an iron axle, 1 in. diam., firmly set, extending 5 ins. above ground, from which bearing trees marked by Thompson:

A fir, 12 ins. diam., bears S.  $75\frac{1}{2}^{\circ}$  E., 52 lks. dist., with healed double blaze.

A madrone, 14 ins. diam., bears South,  $143\frac{1}{2}$  lks. dist., mkd.  $\frac{1}{4}$  S7 3683 BT on double blaze.

To complete the survey of sec. 7, I return to the closing cor. of secs. 7 and 8, on the S. bdy. of sec. 6 and run

N.  $89^{\circ} 58'$  W., on the N. bdy. of sec. 7.

39.28

Point for the  $\frac{1}{4}$  sec. cor. of sec. 7 only, at proportionate distance in departure.

Set an iron post, 28 ins. long,  $2\frac{1}{2}$  ins. diam., 28 ins. in the ground, with brass cap mkd.

*END OK 10/9/2  
 R. BROWN M112-62*

$\frac{1}{4}$  S 7  
 T 30 S R 3 W  
 1965

from which

A white oak, 20 ins. diam., bears S.  $2\frac{1}{2}^{\circ}$  E., 290 lks. dist., mkd.  $\frac{1}{4}$  S7 BT.

A locust, 8 ins. diam., bears West,  $103\frac{1}{2}$  lks. dist., mkd.  $\frac{1}{4}$  S7 BT.