

County Surveyor's Record, Douglas County, Oregon

Subdivision of Section 7, T. 30 S., R. 3 W.

CHAINS	Subdivision of Section 7, T. 30 S., R. 3 W., Will. Meridian, Oregon
	<p>From the $\frac{1}{4}$ sec. cor. of secs. 7 and 18.</p> <p>N. $0^{\circ} 32'$ E., on the N. and S. center line of sec. 7.</p> <p>Descend 190 ft. over NW. slope, through heavy timber and dense undergrowth.</p>
11.60	Ravine, drains S. 80° W.; asc. 90 ft. over SW. slope.
15.50	Spur, slopes N. 60° W.; desc. 185 ft. over N. slope.
19.78	Point for the center S $\frac{1}{16}$ sec. cor. of sec. 7.
	<p>Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;"> $\begin{array}{c} C \\ S \frac{1}{16} S 7 \\ C \\ 1965 \end{array}$ </p>
	<p>from which</p> <p style="padding-left: 40px;">A fir, 6 ins. diam., bears S. $72\frac{1}{2}^{\circ}$ E., 15 lks. dist., mkd. C S$\frac{1}{16}$ S7 BT.</p> <p style="padding-left: 40px;">A fir, 48 ins. diam., bears S. $66\frac{1}{2}^{\circ}$ W., 81 lks. dist., mkd. C S$\frac{1}{16}$ S7 BT.</p>
	<p>Descend 545 ft. over N. slope, changing to NW. slope.</p>
34.30	Enter logged area, edge bears generally E. and W.; continue through scattering timber and dense undergrowth.
37.60	Ravine, drains NW.; desc. 10 ft. over NW. slope.
39.56	Point for the center $\frac{1}{4}$ sec. cor. of sec. 7, at intersection with the E. and W. center line.
	<p>Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;"> $\begin{array}{c} T 30 S R 3 W \\ C \frac{1}{4} S 7 \\ 1965 \end{array}$ </p>
	<p>from which</p> <p style="padding-left: 40px;">A fir, 11 ins. diam., bears S. 71° E., 46 lks. dist., mkd. C $\frac{1}{4}$ S7 BT.</p> <p style="padding-left: 40px;">A white fir, 13 ins. diam., bears S. 41° W., 28 lks. dist., mkd. C $\frac{1}{4}$ S7 BT.</p>
	<p>From this point, a point established by Robert M. Thompson, Registered Engineer, in 1956, bears S. $68^{\circ} 52'$ W., 1.28 chs. dist., monumented with an iron pipe, $1\frac{1}{2}$ ins. diam., firmly set, extending 8 ins. above ground, from which bearing trees marked by Thompson:</p> <p style="padding-left: 40px;">A maple, 16 ins. diam., bears N. 5° W., 12 lks. dist., mkd. C $\frac{1}{4}$ 3683 BT on partly healed double blaze.</p>