

## County Surveyor's Record, Douglas County, Oregon

Subdivision of Section 7, T. 30 S., R. 3 W.

CHAINS	Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.
	SE 1/16 S 7 1965
	from which
	A fir, 15 ins. diam., bears N. 72½° E., 32 lks. dist., mkd. SE1/16 S7 BT.
	A fir, 34 ins. diam., bears N. 35° W., 28 lks. dist., mkd. SE1/16 S7 BT.
	Descend 55 ft. over NE. slope.
21.50	Ravine, drains E.; asc. 20 ft. over SE. slope.
24.00	Spur, slopes E.; desc. 490 ft. over NE. slope.
39.56	The center E 1/16 sec. cor. of sec. 7.
	From the S 1/16 sec. cor. of secs. 7 and 8.
	S. 86° 27' W., on The E. and W. center line of the SE¼ of sec. 7.
	Descend 55 ft. over SW. slope, through heavy timber and dense undergrowth.
2.50	Creek, 1 lk. wide, course N. 35° W.; asc. 35 ft. over NE. slope.
3.60	Spur, slopes N. 30° W.; desc. 80 ft. over NW. slope.
7.15	Bailey Gulch Creek, 2 lks. wide, course N. 20° W.; asc. 470 ft. over E. slope.
19.74	The SE 1/16 sec. cor. of sec. 7.
	Ascend 365 ft. over general E. slope.
28.60	Spur, slopes NE.; desc. 245 ft. over NW. slope.
39.48	The center S 1/16 sec. cor. of sec. 7.
	From the W1/16 sec. cor. of secs. 7 and 18.
	N. 0° 50' E., on the N. and S. center line of the SW¼ of sec. 7.
	Descend 355 ft. over NE. slope, across logged area, through scattering timber and dense undergrowth.
11.75	Creek, 1 lk. wide, course N. 55° W.; asc. 50 ft. over SW. slope.
15.00	Spur, slopes W.; desc. 220 ft. over NW. slope.
39.99	The center W 1/16 sec. cor. of sec. 7.