

CHAINS

Remonumentation of Corner Points, T. 33 S., R. 4 W.

CHAINS

The following field notes describe the remonumentation of certain original corner points of township 33 south, range 4 west, of the Willamette Meridian, Oregon, as provided for in the General Special Instructions, Group Number 350, Oregon, dated May 3, 1957, "Investigation of Collateral or Physical Evidence of Corner Positions and accessories, Followed by Remonumentation of Corner Points, with new accessories when needed".

The history of original corner establishments is referred to at appropriate places in the field notes of the remonumentations.

The remonumentation of original corner points was made at the request of the Medford District Manager for administrative purpose of the Bureau of Land Management.

South boundary, T. 33 S., R. 4 W.,
Willamette Meridian, Oregon

(Remonumenting corners established by Sewall Truax, in 1857)

The cor. of secs. 5, 6, 31 and 32, on the S. bdy. of the Tp., remonumented by Edward F. Sharp, in 1893, with a basalt stone, 20 x 10 x 8 ins., firmly set, 8 ins. in the ground, marked with 4 notches on E. and 2 on W. edges, from which the remaining original bearing trees marked by Truax:

A fir stub and fallen trunk, 18 ins. diam., bears N. 31° E., 33 lks. dist., with healed blaze, which is now opened, revealing the scribe marks 33S R4W S3, on trunk and BT, on fir stub.

A fir stub, 14 ins. diam., bears S. 42° W., 83 lks. dist., with scribe marks BT visible on unhealed blaze. (Record bearing, S. 44° W.)

A sawed fir stump, 36 ins. diam., bears N. 77° W., 42 lks. dist., with no marks remaining. (Record bearing and distance, N. 75° W., 40 lks.)

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap marked

T 33 S R 4 W
S 31 | S 32
S 6 | S 5
T 34 S
1962

from which

A fir, 9 ins. diam., bears N. 27° E., 37 lks. dist., marked T33S R4W S32 BT.

A fir, 14 ins. diam., bears S. 19° E., 78 lks. dist., marked T34S R4W S5 BT.

A fir, 5 ins. diam., bears S. 56° W., 62 lks. dist., marked T34S R4W S6 BT.

A cedar, 10 ins. diam., bears N. 20° W., 72 lks. dist., marked T33S R4W S31 BT.