

County Surveyor's Record, Douglas County, Oregon

13921C

CHAINS

Remonumentation of Corner Points, T. 33 S., R. 4 W.

CHAINS

The cor. of secs. 1, 6, 7, and 12, on the W. bdy. of the Tp., monumented with a basalt stone, 14 x 12 x 8 ins., firmly set, 10 ins. in the ground, marked with 1 notch on N. and 5 on S. edges, from which the remaining original bearing trees:

A fir, 22 ins. diam., bears N. 59° E., 57 lks. dist., with healed blaze.

A pine, 36 ins. diam., bears S. 41° E., 67 lks. dist., with healed blaze.

A madrone, 12 ins. diam., bears N. 21° W., 39 lks. dist., with healed blaze.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap marked

T 33 S
R 5 W R 4 W
S 1 S 6
S 12 S 7
1962

from which

A hemlock, 20 ins. diam., bears S. 50° W., 68 lks. dist., marked T33S R5W S12 BT.

Deposit the original corner stone alongside the iron post.

Subdivisions, T. 33 S., R. 4 W.,
Willamette Meridian, Oregon

(Remonumenting corners established by Edward F. Sharp, in 1893)

The cor. of sec. 25, 26, 35, and 36, monumented with the original corner tree, a fir, 12 ins. diam., with healed blazes on four sides, from which the remaining original bearing trees:

A fir, 22 ins. diam., bears N. 6° E., 17 lks. dist., with healed blaze.

A fir, 12 ins. diam., bears S. 45° E., 13 lks. dist., with scribe marks T33S R4W S26 visible on partly healed blaze.

A fir, 38 ins. diam., bears S. 15° W., 32 lks. dist., with healed blaze.

add a reference monument and a new bearing tree

An iron post, 28 ins. long, 2½ ins. diam., set 22 ins. in the ground, for a reference monument bears S. 62° W., 4 lks. dist., with brass cap marked T33S R4W S35 RM 1962 and an arrow pointing to the corner.

A fir, 6 ins. diam., bears N. 75° W., 43 lks. dist., marked T33S R4W S26 BT.

The sec. cor. of secs. 25 and 26, determined at record bearing and distance from the original bearing trees:

A down fir, 40 ins. diam., bears S. 53° E., 40 lks. dist., with healed blaze.