

County Surveyor's Record, Douglas County, Oregon

CHAINS

Remonumentation of Corner Points, T. 33 S., R. 4 W.

A fir, 38 ins. diam., bears S. 75° W., 13 lks. dist., with healed blaze. Reblaze and mark $\frac{1}{4}$ S1 BT., on bark alongside old blaze.

and a tree not of record:

A cedar, 35 ins. diam., bears N. 43° E., 16 lks. dist., with scribe marks $\frac{1}{4}$ S BT visible on partly healed blaze. Reblaze and mark $\frac{1}{4}$ S6 BT, alongside old blaze.

At the corner point

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins. in the ground with brass cap marked

$\frac{1}{4}$
S 1 S 6
R 4 W R 3 W
T 33 S
1962

Reset the iron pipe alongside the iron post.

West boundary, T. 33 S., R. 4 W.,
Willamette Meridian, Oregon

(Remonumenting corners established by Edward F. Sharp, in 1893)

The cor. of secs. 25, 30, 31, and 36, on the W. bdy. of the Twp., perpetuated by Norman D. Price, in 1955, with an iron pipe, 3 ft. long, 2 ins. diam., firmly set 2 ft. in the ground, from which the remaining original bearing trees:

A cedar, 32 ins. diam., bears N. 46° E., 51 lks. dist., with scribe marks T33S R4W S30 BT visible on unhealed blaze.

A cedar, 14 ins. diam., bears S. 64° W., 37 lks. dist., with scribe marks T33S R5W S36 BT visible on unhealed blaze. (Record bearing, S. 58° W.)

and bearing trees marked by Norman D. Price:

A cedar, 9 ins. diam., bears S. 67° E., 115 lks. dist., with scribe marks T33S R4W S31 BT visible on unhealed blaze.

A fir, 40 ins. diam., bears N. 51° W., 21 lks. dist., with scribe marks T33S R5W S25 R33 BT visible on unhealed blaze.

At the corner point

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins. in the ground, with brass cap marked

T 33 S
R 5 W R 4 W
S 25 S 30
S 36 S 31
1962

Reset the iron pipe alongside the iron post.