

County Surveyor's Record, Douglas County, Oregon

Remonumentation of Corner Points, T. 33 S., R. 4 W.

CHAINS

from which

A tan oak, 5 ins. diam., bears N. 69° E., 43 lks.
dist., marked $\frac{1}{4}$ S10 BT.

The $\frac{1}{4}$ sec. cor. of secs. 9 and 10, monumented with a basalt stone, 12 x 10 x 6 ins., firmly set 10 ins. in the ground, marked $\frac{1}{4}$ on W. face, from which the original bearing trees:

A down fir, 14 ins. diam., bears N. 40° E., 11 lks.
dist., with scribe marks $\frac{1}{4}$ S visible on partly
healed blaze. (Record bearing, N. 47° E.)

A fir snag, 28 ins. diam., bears N. 70° W., 28 lks.
dist., with scribe marks $\frac{1}{4}$ S BT visible on
opened blaze. (Record bearing, N. 73° W.)

At the corner point

Set an iron post, 28 ins. long, 2 $\frac{1}{2}$ ins. diam., 18 ins. in
the ground to bedrock, and in a mound of stone, 3 ft.
base, to top, with brass cap marked

$\frac{1}{4}$
S 9 S 10
T 33 S R 4 W
1962

from which

A hemlock, 8 ins. diam., bears N. 44 $\frac{1}{2}$ ° E., 32 lks.
dist., marked $\frac{1}{4}$ S10 BT.

A hemlock, 16 ins. diam., bears N. 21° W., 47 lks.
dist., marked $\frac{1}{4}$ S9 BT.

Deposit the original corner stone alongside the
iron post.

The cor. of secs. 3, 4, 9, and 10, determined at record
bearing and distance from the original bearing trees:

A fir, 18 ins. diam., bears N. 51° E., 39 lks. dist.,
with scribe marks T33S R4W S3 B visible on partly
healed blaze.

A fir snag, 12 ins. diam., bears S. 31° E., 35 lks.
dist., with scribe marks T33S R4W S10 visible on
partly healed blaze.

A fir, 18 ins. diam., bears S. 86° W., 73 lks.
dist., with scribe marks T33S R4W S9 BT visible
on opened blaze.

A fir, 34 ins. diam., bears N. 35° W., 44 lks. dist.,
with scribe marks T33S R4W S visible on partly
healed blaze.

At the corner point

Set an iron post, 28 ins. long, 2 $\frac{1}{2}$ ins. diam., 22 ins.
in the ground, with brass cap marked

T 33 S R 4 W
S 4 S 3
S 9 S 10
1962