

## County Surveyor's Record, Douglas County, Oregon

Remonumentation of Corner Points, T. 33 S., R. 4 W.

CHAINS

from which

A fir, 12 ins. diam., bears S.  $25\frac{1}{2}^{\circ}$  E., 34 lks. dist., marked T33S R4W S10 BT.

From this point an iron pipe, 1 in. diam., protruding 8 ins. above ground, not of record, bears North 11 lks. distant.

The  $\frac{1}{4}$  sec. cor. of secs. 3 and 10, monumented with a basalt stone, 18 x 12 x 8 ins., lying on surface of the ground, marked  $\frac{1}{4}$  on one face, from which the original bearing trees:

A fir, 30 ins. diam., bears N.  $64\frac{1}{2}^{\circ}$  W., 75 lks. dist., with healed blaze. Reblaze and mark  $\frac{1}{4}$  S3 BT, alongside old blaze.

A fir, 24 ins. diam., bears S.  $75^{\circ}$  E., 25 lks. dist., with partly healed and burned blaze, which is now opened, revealing the scribe marks  $\frac{1}{4}$  S.

At the corner point

Set an iron post, 28 ins. long,  $2\frac{1}{2}$  ins. diam., 22 ins. in the ground, with brass cap marked

$$\frac{1}{4} \frac{S 3}{S 10}$$

T 33 S R 4 W  
1962

from which

A madrone, 8 ins. diam., bears S.  $48\frac{1}{2}^{\circ}$  W., 72 lks. dist., marked  $\frac{1}{4}$  S10 BT.

deposit the original corner stone alongside the iron post.

The  $\frac{1}{4}$  sec. cor. of secs. 3 and 4, monumented with the original corner tree, a hemlock snag, 25 ins. diam., with scribe marks  $\frac{1}{4}$  S visible on opened blaze on W. side, from which the original bearing trees:

A hemlock, 14 ins. diam., bears N.  $7^{\circ}$  E., 17 lks. dist., with scribe marks  $\frac{1}{4}$  S BT visible on unhealed blaze. Reblaze and mark  $\frac{1}{4}$  S3 BT, alongside old blaze.

A hemlock snag, 25 ins. diam., bears S.  $37^{\circ}$  W., 38 lks. dist., with scribe marks  $\frac{1}{4}$  S visible on partly healed blaze. (Record distance, 28 lks.)

Add new bearing tree and a reference monument:

A hemlock, 9 ins. diam., bears S.  $63^{\circ}$  W., 27 lks. dist., marked  $\frac{1}{4}$  S4 BT.

An iron post, 28 ins. long,  $2\frac{1}{2}$  ins. diam., set 22 ins. in the ground, for a reference monument, bears N.  $13^{\circ}$  W.,  $4\frac{1}{2}$  lks. dist., with brass cap marked T33S R4W  $\frac{1}{4}$ S 4RM 1962 and an arrow pointing to the corner.

The  $\frac{1}{4}$  sec. cor. of secs. 21 and 28, determined at record bearing and distance from the original bearing trees: