

## County Surveyor's Record, Douglas County, Oregon

## Remonumentation of Corner Points, T. 33 S., R. 4 W.

CHAINS

A fir, 45 ins. diam., bears N. 73° W., 30 lks. dist., with scribe marks  $\frac{1}{4}$  S visible on partly healed blaze. Reblaze and mark  $\frac{1}{4}$  S21 BT, alongside old blaze.

A fir, 45 ins. diam., bears S. 39° E., 35 lks. dist., with no marks remaining on unhealed blaze. Reblaze and mark  $\frac{1}{4}$  S28 BT alongside old blaze.

At the corner point

Set an iron post, 28 ins. long,  $2\frac{1}{2}$  ins. diam., 22 ins. in the ground, and in a mound of stone, 3 ft. base, to top, with brass cap marked

$$\begin{array}{c} \frac{1}{4} \text{ S } 21 \\ \frac{1}{4} \text{ S } 28 \\ \text{T } 33 \text{ S } \text{ R } 4 \text{ W} \\ 1962 \end{array}$$

The  $\frac{1}{4}$  sec. cor. of secs. 8 and 9, perpetuated with an iron pipe, 3 ft. long, 1 in. diam., firmly set, 8 ins. in the ground, and in a mound of stone, 3 ft. base, 2 ft. high, with brass cap marked

$$\begin{array}{c} \text{T } 33 \text{ S } \text{ R } 4 \text{ W} \\ \frac{1}{4} \\ \text{S } 8 \text{ S } 9 \\ \text{RE } 240 \\ 1955 \end{array}$$

from which the remaining original bearing tree:

A dead fir, 30 ins. diam., bears N. 50° E., 26 lks. dist., with scribe marks  $\frac{1}{4}$  S visible on partly healed blaze.

and a bearing tree not of record:

A fir, 8 ins. diam., bears N. 30 $\frac{1}{2}$ ° W., 79 lks. dist., with scribe marks  $\frac{1}{4}$  S BT visible on unhealed blaze.

add new bearing trees:

A fir, 25 ins. diam., bears S. 82° E., 25 lks. dist., marked  $\frac{1}{4}$  S9 BT.

A fir, 10 ins. diam., bears S. 11° W., 76 lks. dist., marked  $\frac{1}{4}$  S8 BT.

I add the marks B L M 1962, to the brass cap.

The cor. of secs. 4, 5, 8, and 9, monumented with a basalt stone, 20 x 12 x 10 ins, firmly set 10 ins. in the ground, marked with 5 notches on S. and 4 on E. edges, from which the original bearing trees:

A fir, 30 ins. diam., bears N. 30° E., 25 lks. dist., with a healed blaze.

A fir, 24 ins. diam., bears S. 60° E., 23 lks. dist., with a healed blaze.

A fir, 20 ins. diam., bears S. 50° W., 72 lks. dist., with a healed blaze.

A down fir, 25 ins. diam., bears N. 19° W., 38 lks. dist., with scribe marks T33S R visible on partly healed blaze.