

Remonumentation of Corner Points, T. 33 S., R. 4 W.

CHAINS

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, and in a mound of stone, 2 ft. base, to top, with brass cap marked

T 33 S R 4 W
 S 5 S 4
 S 8 S 9
 1962

from which

A fir, 9 ins. diam., bears N. 59° W., 80 lks. dist., marked T33S R4W S5 BT.

Deposit the original corner stone alongside the iron post.

The ¼ sec. cor. of secs. 31 and 32, determined at record bearing and distance from the original bearing trees:

A fir, 24 ins. diam., bears S. 76° E., 42 lks. dist., with scribe marks ¼ S visible on opened blaze. Reblaze and mark ¼ S32 BT, alongside old blaze.

A cedar, 14 ins. diam., bears S. 79° W., 17 lks. dist., with scribe marks ¼ S BT visible on unhealed blaze. Reblaze and mark ¼ S31 BT, alongside old blaze.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, and in a mound of stone, 2 ft. base, to top, with brass cap marked

¼
 S 31 S 32
 T 33 S R 4 W
 1962

The cor. of secs. 29, 30, 31, and 32, determined at record bearing and distance from the original bearing trees:

A fir, 14 ins. diam., bears N. 9° E., 76 lks. dist., with scribe marks T33S R4W S29 BT visible on unhealed blaze. (Record distance, 74 lks.)

A fir, 60 ins. diam., bears S. 18° E., 11 lks. dist., with illegible scribe marks visible on opened and burned blaze. Reblaze and mark T33S R4W S32 BT.

A fir snag, 24 ins. diam., bears S. 61° W., 11 lks. dist., with scribe marks T33S R4W S31 BT visible on burned face of unhealed blaze.

A fir stub, 20 ins. diam., bears N. 44° W., 17 lks. dist., with no marks remaining.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap marked