

County Surveyor's Record, Douglas County, Oregon

Remonumentation of Corner Points, T. 33 S., R. 4 W.

CHAINS

T 33 S R 4 W
 $\frac{1}{4}$ 30 S 29
 S 31 S 32
 1962

from which

A madrone, 6 ins. diam., bears S. 37° W., 18 lks. dist., marked T33S R4W S31 BT.

A live oak, 6 ins. diam., bears N. 62½° W., 20 lks. dist., marked T33S R4W S30 BT.

The ¼ sec. cor. of secs. 29 and 32, monumented with a basalt stone, 12 x 12 x 6 ins., firmly set 10 ins. in the ground, marked ¼ on N. face, from which the remaining original bearing tree:

A down fir, 14 ins. diam., bears N. 50° W., 121 lks. dist., with no marks remaining. (Record bearing and distance, N. 45° W., 117 lks.)

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap marked

¼ $\frac{S 29}{S 32}$
 T 33 S R 4 W
 1962

from which

A pine, 10 ins. diam., bears N. 25½° W., 26 lks. dist., marked ¼ S29 BT.

A fir, 10 ins. diam., bears S. 54° W., 64 lks. dist., marked ¼ S32 BT.

Deposit the original corner stone alongside the iron post.

The cor. of secs. 7, 8, 17, and 18, monumented with a basalt stone, 18 x 10 x 8 ins., firmly set 8 ins. in the ground, marked with 4 notches on S. and 5 on E. edges, from which the remaining original bearing trees:

A fir, 30 ins. diam., bears S. 42° E., 18 lks. dist., with no marks remaining on opened blaze. Reblaze and mark T33S R4W S17 BT, alongside old blaze. (Record bearing & distance, S. 29° E., 13 lks.)

A sawed fir stump, 25 ins. diam., bears S. 80° W., 15 lks. dist., with no marks remaining.

A down fir, 25 ins. diam., bears N. 62° W., 60 lks. dist., with no marks remaining.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, and in a mound of stone, 2 ft. base, to top, with brass cap marked

T 33 S R 4 W
 $\frac{S 7 S 8}{S 18 S 17}$
 1962