

# County Surveyor's Record, Douglas County, Oregon

18929B

Remonumentation of Certain Original Corner Points,  
T. 33 S., R. 4 W., Willamette Meridian, Oregon

CHAINS CHAINS

The  $\frac{1}{4}$  sec. cor. of secs. 17 and 20, monumented with the original basalt stone, 16 x 10 x 6 ins., firmly set 11 ins. in the ground, and in a mound of stone, 2 ft. base, to top, mkd.  $\frac{1}{4}$  on N. face, from which the original bearing trees:

A cedar, 27 ins. diam., bears N. 10° E., 27 lks. dist., with scribe marks  $\frac{1}{4}$  visible on partially healed blaze.

A root hole, bears S. 32° W., 53 lks. dist., alongside of which is lying a rotted fir, 24 ins. diam., with scribe marks  $\frac{1}{4}$  S visible on partly opened blaze.

At the corner point

Set an iron post, 28 ins. long, 2 $\frac{1}{2}$  ins. diam., 20 ins. in the ground; to solid rock, and in a mound of stone, 2 ft. base, to top, with brass cap mkd.

T 33 S R 4 W  
 $\frac{1}{4}$  S 17  
 $\frac{1}{4}$  S 20  
1968

from which new bearing trees

A fir, 6 ins. diam., bears N. 60° W., 31 lks. dist., mkd.  $\frac{1}{4}$  S17 BT.

A fir, 6 ins. diam., bears S. 27° W., 42 lks. dist., mkd.  $\frac{1}{4}$  S20 BT.

Deposit original stone alongside iron post.

The  $\frac{1}{4}$  sec. cor. of secs. 7 and 18, determined at the center of the root hole of the original corner tree, alongside of which is lying the corner tree, a yew, 5 ins. diam., mkd.  $\frac{1}{4}$  S on partially healed blaze, from which the remaining original bearing tree:

A white fir, 18 ins. diam., bears S. 45° E., 14 lks. dist., with healed blaze. (Record, 24 lks.)

At the corner point

Set an iron post, 28 ins. long, 2 $\frac{1}{2}$  ins. diam., 24 ins. in the ground, with brass cap mkd.

T 33 S R 4 W  
 $\frac{1}{4}$  S 7  
 $\frac{1}{4}$  S 18  
1968

from which a new bearing tree

A white fir, 7 ins. diam., bears N. 27 $\frac{1}{2}$ ° W., 35 lks. dist., mkd.  $\frac{1}{4}$  S7 BT.

*Jack Co*