

County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey, Portion of E. Bdy., T. 28 S., R. 4 W.

CHAINS	<p>and a local bearing tree</p> <p style="margin-left: 40px;">A maple, 11 ins. diam., bears S. <math>33\frac{1}{2}^\circ</math> W., 49 lks. dist., with scribe marks S24 BT visible on partly healed double blaze.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, <math>2\frac{1}{2}</math> ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <table style="margin: auto; border-collapse: collapse;"> <tr><td>T 28 S</td></tr> <tr><td>R 4 W R 3 W</td></tr> <tr><td style="border-left: 1px solid black; border-right: 1px solid black;">S 13   S 18</td></tr> <tr><td style="border-left: 1px solid black; border-right: 1px solid black;">S 24   S 19</td></tr> <tr><td>1965</td></tr> </table> </div> <p>Reset iron pipe alongside the iron post.</p> <p>N. <math>0^\circ 06'</math> E., bet. secs. 13 and 18, marking and blazing the true line.</p> <p>Ascend 285 ft. over broken SE. slope, through heavy timber and dense undergrowth.</p> <p>15.00 Ridge, dividing Riser Creek and Buck Fork of North Myrtle Creek drainage, bears E. and W.; desc. 210 ft. over N. slope.</p> <p>19.57 Point for the S 1/16 sec. cor. of secs. 13 and 18.</p> <p>Set an iron post, 28 ins. long, <math>2\frac{1}{2}</math> ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <table style="margin: auto; border-collapse: collapse;"> <tr><td>S 1/16</td></tr> <tr><td style="border-left: 1px solid black; border-right: 1px solid black;">S 13   S 18</td></tr> <tr><td>1965</td></tr> </table> </div> <p>from which</p> <p style="margin-left: 40px;">A hemlock, 24 ins. diam., bears N. <math>63\frac{1}{2}^\circ</math> E., 29 lks. dist., marked S 1/16 S18 BT.</p> <p style="margin-left: 40px;">A fir, 8 ins. diam., bears N. <math>59^\circ</math> W., 65 lks. dist., marked S 1/16 S13 BT.</p> <p>Descend 470 ft. over broken NE. slope, changing to N. slope.</p> <p>33.20 Buck Fork of North Myrtle Creek, 10 lks. wide, course W., also leave timber, enter pasture land, edge bears E. and W.; ascend 45 ft. over S. slope.</p> <p>36.64 Barbed wire fence, bears E. and W.</p> <p>36.90 Black top road, 30 lks. wide, bears E. and W.</p> <p>37.25 Barbed wire fence, bears E. and W.</p> <p>39.14 The <math>\frac{1}{4}</math> sec. cor. of secs. 13 and 18, reestablished at proportionate distance by James W. Byron, Deputy County Surveyor, in 1955, monumented with an iron post, 1 in. diam, firmly set, extending 6 ins. above ground, with brass cap mkd.</p>	T 28 S	R 4 W R 3 W	S 13   S 18	S 24   S 19	1965	S 1/16	S 13   S 18	1965
T 28 S									
R 4 W R 3 W									
S 13   S 18									
S 24   S 19									
1965									
S 1/16									
S 13   S 18									
1965									