

County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey, Portion of E. Bdy., T. 28 S., R. 4 W.

CHAINS

COUNTY SURVEYORS OFFICE

$\frac{1}{2}$  S  
 T 28 S | T 28 S  
 R 4 W | R 3 W  
 S 13 | S 18  
 1955

F.D.C.  
 F.D. 10/81  
 W. RUPPERT  
 M 89-20  
 F.D. BC  
 7/93  
 R 30-110  
 M 17-39

from which bearing trees marked by Byron

A cedar, 22 ins. diam., bears N. 81° E., 247 lks. dist., with scribe marks  $\frac{1}{2}$  S18 SC BT visible on partly healed double blaze.

A maple, 30 ins. diam., bears N. 34° W., 159 lks. dist., with scribe marks  $\frac{1}{2}$  S B visible on partly healed double blaze.

Add marks HLM 1965 to brass cap.

N. 0° 06' E., beginning new measurement.

Ascend 520 ft. over broken S. slope, across open pasture land.

- 2.31 Intersect the S. side of a wood frame house 48 ft. x 24 ft., 13 lks. W. of the S.E. corner, long side bears E. and W.
- 3.70 Enter heavy young timber and dense undergrowth, edge bears E. and S. W., continue along the W. edge of logged area.
- 20.00 Enter logged area, edges bear S. and W.
- 22.50 Spur, slopes S.W.; desc. 70 ft. over N. W. slope.
- 33.75 Spring branch, 1 lk. wide, course S. W.; asc. 200 ft. over S. slope.
- 36.00 Spur, slopes S. W. ; asc. 5 ft. along W. slope.
- 39.10 The cor. of secs. 7, 12, 13 and 18, perpetuated and recorded by James W. Byron, Deputy County Surveyor, in 1961, monumented with an iron pipe 1 in. diam., firmly set, extending 8 ins. above ground, alongside of which is an iron post 1 in. diam., firmly set, extending 16 ins. above ground, with brass cap mkd.

COUNTY SURVEYORS OFFICE

T 28 S  
 R 4 W | R 3 W  
 S 12 | S 7  
 S 13 | S 18  
 1961

from which the original bearing trees

A madrone, 38 ins. diam., bears N. 59° E., 58 lks. dist., with scribe marks 8 BT visible on partly healed blaze. (Record, N. 55° E., 65 lks.)

A madrone, 30 ins. diam., bears S. 85° E., 44 lks. dist., with scribe marks T28S R3 BT visible on partly healed blaze. (Record, 54 lks.)