

County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey, Portion of the E. Bdy., T. 28 S., R. 4 W.

CHAINS

A rotted fir snag, 35 ins. diam., bears S. 40° W.,
42 lks. dist., with no marks visible. (Record,
S. 44° W., 37 lks.)

A fire damaged cedar, 60 ins. diam., bears N. 70° W.,
45 lks. dist., with scribe marks S12 visible on
new blaze, no original marks visible.

and bearing trees marked by Byron

A fir, 15 ins. diam., bears S. 37° E., 37 lks.
dist., with illegible scribe marks visible on
partly healed double blaze.

and a bearing tree of which I have no record

A madrone, 20 ins. diam., bears S. 55° W., 35 lks.
dist., with scribe marks S 3 28S R4W 2880 visible
on partly healed blaze.

Add marks BLM 1965 to brass cap.

Land, mountainous.

Soil, rocky clay loam.

Timber, fir, white fir, hemlock, cedar, madrone, yew,
chinquapin, oak, maple, and ash; undergrowth, poison oak,
ocean spray, vine maple, fern, Oregon grape, manzanita,
salal, and hazel.

Dependent Resurvey of Portion of the Subdivisional Lines
T. 28 S., R. 4 W., Willamette Meridian, Oregon.

(Restoring the 1881 survey by William W. Byars.)

From the $\frac{1}{4}$ sec. cor. of secs. 23 and 24, monumented with
an iron post, 2 $\frac{1}{2}$ ins. diam., firmly set, extending 3 ins.
above ground, marked and witnessed as described in the
official record of the 1958 resurvey.

N. 1° 15' W., bet. secs. 23 and 24, marking and blazing
the true line.

Descend 5 ft. over nearly level bottom land, across
logged area, through scattering timber and dense
undergrowth.

- 2.70 North Fork of Myrtle Creek, 20 lks. wide, course S. 60° W.;
asc. 330 ft. over S. E. slope.
- 11.40 Gravelled road, 25 lks. wide, bears N. E. and S. W.
- 29.00 Spur, slopes S. 60° E.; desc. 115 ft. over N. E. slope.
- 30.65 Creek, 1 lk. wide, course S.E.; asc. 25 ft. over S. slope.
- 32.00 Creek, 1 lk. wide, course S. 30° E.; asc. 100 ft. over
S. W. slope.
- 39.11 Point for the cor. of secs. 13, 14, 23 and 24, at proportionate
distance; there is no remaining evidence of the original
corner.
- Set an iron post, 28 ins. long, 2 $\frac{1}{2}$ ins. diam., 22 ins.
in the ground, with brass cap mkd.