

Dependent Resurvey, Portion of the Subdivision Lines, T. 28 S., R. 4 W.

CHAINS

T 28 S R 4 W  
 $\frac{S 14}{S 23} | \frac{S 13}{S 24}$   
 1965

from which

A madrone, 12 ins. diam., bears N. 65° E., 76 lks.  
 dist., marked T28S R4W S13 BT.

A fir, 9 ins. diam., bears S. 65½° E., 49½ lks.  
 dist., marked T28S R4W S24 BT.

A madrone, 28 ins. diam., bears S. 78° W., 91 lks.  
 dist., marked T28S R4W S23 BT.

A madrone, 10 ins. diam., bears N. 29½° W., 32 lks.  
 dist., marked T28S R4W S14 BT.

Land, mountainous.

Soil, rocky clay loam.

Timber, fir, white fir, hemlock, cedar, madrone, yew,  
 chinquapin, oak, maple, and ash; undergrowth, poison oak,  
 ocean spray, vine maple, fern, Oregon grape, manzanita,  
 salal, and hazel.

From the cor. of secs. 13, 18, 19 and 24, on the E. bdy.  
 of the Township.

S. 89° 02' W., bet. secs. 13 and 24.

Ascend 55 ft. over SE. slope, through heavy timber and  
 dense undergrowth.

3.80 Spur, slopes S.; desc. 65 ft. over S. W. slope.

7.60 Ravine, drains S. 20° E.; asc. 340 ft. over broken S. E.  
 slope.

19.56 Point for the E 1/16 sec. cor. of secs. 13 and 24.

Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins.  
 in the ground, with brass cap mkd.

E 1/16  $\frac{S 13}{S 24}$   
 1965

from which

A fir, 14 ins. diam., bears N. 39° W., 79 lks.  
 dist., marked E 1/16 S13 BT.

A fir, 28 ins. diam., bears S. 27° E., 7 lks.  
 dist., marked E 1/16 S24 BT.

Ascend 35 ft. over S. E. slope.

21.75 Ridge, dividing North Myrtle Creek and Riser Creek  
 drainages, bears N. E. and S. W.; desc. 600 ft. over broken  
 W. slope.

39.12 The ¼ sec. cor. of secs. 13 and 24, perpetuated and  
 recorded by James W. Byron, Deputy County Surveyor,  
 in 1957, monumented with an iron bar, 1¼ x 2½ ins.,  
 firmly set, extending 14 ins. above the ground, alongside  
 of which is an iron post, 1 in. diam., firmly set,  
 extending 14 ins. above the ground, with brass cap mkd.