

Dependent Resurvey, Subdivisional Lines, T. 28 S., R. 4 W.

CHAINS

N.  $0^{\circ} 19'$  W., bet. secs. 13 and 14.

Ascend 120 ft. over S. slope, generally along the East edge of logged area, through heavy timber and dense undergrowth.

5.50 Spur, slopes S.  $60^{\circ}$  E.; desc. 260 ft. over N. E. slope.

14.35 Creek, 2 lks. wide, course S. E.; asc. 150 ft. over S. W. slope.

18.70 Dirt road, 10 lks. wide, bears N. W. and S. E.

19.55 Point for the S  $1/16$  sec. cor. of secs. 13 and 14.Set an iron post, 28 ins. long,  $2\frac{1}{2}$  ins. diam., 23 ins. in the ground, with brass cap mkd.
$$\begin{array}{c} \text{S } 1/16 \\ \text{S } 14 | \text{S } 13 \\ 1965 \end{array}$$

from which

A chinquapin, 6 ins. diam., bears N.  $37^{\circ}$  E., 50 lks. dist., marked S  $1/16$  S13 BT.A madrone, 8 ins. diam., bears N.  $16\frac{1}{2}^{\circ}$  W., 66 lks. dist., marked S  $1/16$  S14 BT.

Ascend 255 ft. over S. W. slope.

29.325 Point for the N-S  $1/64$  sec. cor. of secs. 13 and 14.Set an iron post, 28 ins. long,  $2\frac{1}{2}$  Ins. diam., 22 ins. in the ground, with brass cap mkd.
$$\begin{array}{c} \text{N} - \text{S} \\ 1/64 \\ \text{S } 14 | \text{S } 13 \\ 1965 \end{array}$$

from which

A fir, 32 ins. diam., bears N.  $60\frac{1}{2}^{\circ}$  E., 48 lks. dist., marked N-S  $1/64$  S13 BT.A Chinquapin, 10 ins. diam., bears N.  $46^{\circ}$  W., 54 lks. dist., marked N=S  $1/64$  S14 BT.

Ascend 55 ft. over S.W. slope.

31.40 Spur, slopes S.  $60^{\circ}$  E.; desc. 215 ft. over N. E. slope.39.10 The  $\frac{1}{4}$  sec. cor. of secs. 13 and 14, perpetuated and recorded by James W. Byron, Deputy County Surveyor in 1961, monumented with an iron post, 1 in. diam., firmly set, extending 12 ins. above the ground, with brass cap marked
$$\begin{array}{c} \text{COUNTY SURVEYOR OFFICE} \\ \text{T } 28 \text{ S } \text{ R } 4 \text{ W} \\ \frac{1}{4} \\ \text{S } 14 | \text{S } 13 \\ 1961 \end{array}$$