

County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey, Subdivisional Lines, T. 28 S., R. 4 W.

CHAINS

from which the remaining original bearing tree

A down fir, 48 ins. diam., bears N. 35° E., 60 lks. dist., with fragmentary scribe marks visible on bark blaze.

and a bearing tree marked by Byron

a fir, 11 ins. diam., bears N. 75° E., 36 lks. dist., with fragmentary scribe marks visible on partly healed double blaze.

and a bearing tree of which I have no record

A hemlock, 18 ins. diam., bears S. 55° W., 18 lks. dist., with healed double blaze.

Add marks HLM 1965 to brass cap.

N. 0° 14' W., beginning new measurement.

Descend 80 ft. over N. E. slope, along W. edge of logged area.

- 2.00 Ravine, drains N. 75° E.; asc. 35 ft. over S.E. slope.
- 6.60 Spur, slopes S. 80° E.; desc. 205 ft. over N. E. slope.
- 14.40 Creek, 1 lk. wide, course S. 60° E.; asc. 350 ft. over S. slope.
- 26.20 Spur, slopes S. 80° E.; desc. 95 ft. over N. E. slope.
- 29.90 Ravine, drains N. 80° E.; asc. 40 ft. over S. E. slope.
- 32.60 Spur, slopes E.; desc. 320 ft. over N. E. slope.
- 39.50 Creek, 1 lk. wide, course N. 70° E.; asc. 7 ft. over S. E. slope.
- 39.75 The cor. of secs. 11, 12, 13, and 14, perpetuated and recorded by James W. Byron, Deputy County Surveyor, in 1961, monumented with an iron post, 1 in. diam., firmly set, extending 12 ins. above the ground, with brass cap marked

COUNTY SURVEYORS OFFICE

T 28 S R 4 W

S 11 | S 12

S 14 | S 13

1961

from which the remaining original bearing trees

A fir, 60 ins. diam., bears S. 7° E., 45 lks. dist., with scribe marks S13 T28S R4W BT visible on bark blaze. (Record, S. 2° E.)

A fir, 62 ins. diam., bears N. 15° W., 35 lks. dist., with scribe marks S11 visible on bark blaze.

and bearing trees marked by Byron

An alder, 13 ins. diam., bears N. 59° E., 32 lks. dist., with scribe marks T28S R4W S12 CS BT. visible on partly healed blaze.