

## County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey, Subdivisional Lines, T. 28 S., R. 4 W.

## CHAINS

A cedar, 28 ins. diam., bears S. 70° W., 86 lks. dist., with scribe marks  $\frac{1}{4}$  S13 CS visible on partly healed double blaze.

and a new bearing tree

A cedar, 12 ins. diam., bears N. 22½° W., 49 lks. dist., marked  $\frac{1}{4}$  S12 BT.

Add marks ELM 1965 to brass cap.

---

N. 89° 40' W., beginning new measurement.

Ascend 90 ft. over S.E. slope, across logged area, through scattering timber and dense undergrowth.

- 6.30 Top of ascent, slopes S.; desc. 25 ft. over S.W. slope.  
 7.40 Dirt road, 25 lks. wide, bears N. 40° W. and S. 40° E.  
 9.00 Ravine, drains S. 10° E.; asc. 125 ft. over S.E. slope.  
 15.30 Spur, slopes S.; desc. 95 ft. over S.W. slope.  
 19.98 The W 1/16 sec. cor. of secs. 12 and 13, established and recorded by Ben B. Irving, County Surveyor, in 1921, and now determined at record bearing and distance, from Irving's bearing trees:

A cedar, 20 ins. diam., bears N. 39½° W., 56 lks. dist., with scribe marks 1-6 S visible on partly healed double blaze.

A sawed fir stump, 24 ins. diam., bears S. 17° E., 21 lks. dist., no marks visible.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.

$$\begin{array}{c} \text{W } 1/16 \text{ } \frac{\text{S } 12}{\text{S } 13} \\ 1965 \end{array}$$

from which a new bearing tree

A fir, 9 ins. diam., bears S. 31° E., 46 lks. dist., marked W 1/16 S13 BT.

- 
- S. 8 S. 89° 47' W., beginning new measurement.  
 Descend 150 ft. over S. W. slope.  
 6.55 Dirt road, 20 lks. wide, bears N. and S.  
 9.80 North Myrtle Creek, 10 lks. wide, course S. 40 E.; asc. 105 ft. over N. E. slope.  
 19.40 Creek, 1 lk. wide, course N. 60° E.; asc. 10 ft. over S. E. slope.  
 19.89 The cor. of secs. 11, 12, 13, and 14.