

## County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey, Subdivisional Lines, T. 28 S., R. 4 W.

CHAINS

A sawed fir stump, 26 ins. diam., bears N. 50 3/4° W.,  
73 lks. dist., with healed blaze.

Add a new bearing tree

A hemlock, 8 ins. diam., bears S. 39° E., 64 lks.  
dist., marked T28S R4W S22 BT.

Land, mountainous.

Soil, rocky clay loam.

Timber, fir, white fir, hemlock, cedar, madrone, yew,  
chinquapin, oak, maple, and dogwood; undergrowth, vine  
maple, poison oak, ocean spray, fern Oregon grape, salal  
willow, manzanita, blackberry and hazel.

Subdivision of Section 13, T. 28 S., R. 4 W.,  
Willamette Meridian, Oregon

From the 1/4 cor. of secs. 13 and 24.

N. 0° 03' E., on the N. and S. center line of sec. 13.

Descend 95 ft. over broken N.W. slope, along the E. edge  
of logged area, through heavy timber and dense undergrowth.

19.73 Point for the center s 1/16 sec. cor. of sec. 13.

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins.  
in the ground, with brass cap mkd.

C  
S 1/16 | S 13  
C  
1965

from which

A fir, 13 ins. diam., bears N. 60° E., 52 lks.  
dist., marked CS 1/16 S13 BT.

A fir, 8 ins. diam., bears N. 60° W., 8 lks.  
dist., marked CS 1/16 S13 BT.

Descend 90 ft. over broken N.W. slope.

25.50 Buck Fork of North Myrtle Creek, 12 lks. wide, course S.  
70° W.; enter logged area, edge bears generally S. and E.;  
ascend 235 ft. over S.E. slope.

27.25 Gravelled road, 30 lks. wide, bears E. and W.

39.46 Point for the center 1/4 sec. cor. of sec. 13, at  
intersection with the E. and W. center line.

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 26 ins.  
in the ground, with brass cap mkd.

T 28 S R 4 W  
C 1/4 S 13  
1965

from which

A fir, 7 ins. diam., bears S. 19° E., 98 lks.  
dist., marked C 1/4 S13 BT.

A fir, 28 ins. diam., bears S. 39° W., 50 lks.  
dist., marked C 1/4 S13 BT.