

Subdivision of Section 13, T. 28 S., R. 4 W.

CHAINS	
	Ascend 270 ft. over S.E. slope.
43.55	Dirt road, 20 lks. wide, bears N. 80° E. and S. 80° W.
47.50	Spur, slopes S.W.; desc. 255 ft. over broken N.W. slope.
50.25	Same dirt road, 20 lks. wide, bears N. 50° E. and S. 50° W.
62.00	Ravine, drains S. 80° W.; asc. 100 ft. over S.E. slope.
67.50	Spur, slopes W.; desc. 230 ft. over N.W. Slope.
78.15	Creek, 4 lks. wide, course S. 40° W.; asc. 15 ft. over S.E. slope.
78.76	The $\frac{1}{4}$ sec. cor. of secs. 12 and 13.
	From the $\frac{1}{4}$ sec. cor. of secs. 13 and 18, on the E. bdy. of the Township.
	S. 89° 26' W., on the E. and W. center line of sec. 13.
	Descend 15 ft. along a broken S. slope, across pasture land.
1.80	Woven wire fence, bears N.E. and S.W.
2.008	Dirt driveway, 20 lks. wide, bears N.E. and S.W.
7.14	Woven wire fence, bears N. and S.
10.93	From this point, the S.E. corner of an old log house, bears North, 0.06 chs. dist., dimensions $31\frac{1}{2} \times 17$ ft., long side bears E. and W.
11.00	Creek, 2 lks. wide, course S. 15° W.; asc. 15 ft. along broken S. slope.
11.78	Woven wire fence, bears N. 15° E. and S. 15° W.
16.55	Woven wire fence, bears N. 15° E. and S. 15° W., leave pasture, enter logged area, with scattering timber and light undergrowth, edge bears same as fence.
19.58	Point for the center E $\frac{1}{16}$ sec. cor. of sec. 13.
	Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.
	C $\frac{E \frac{1}{16}}{S 13}$ C 1965
	from which
	A cedar, 18 ins. diam., bears N. 35° E., 14 lks. dist., marked CE $\frac{1}{16}$ S13 BT.
	A fir, 15 ins. diam., bears S. 69° W., 57 lks. dist., marked CE $\frac{1}{16}$ S13 BT.
	from this point, angle point No. 1 of tract No. 37, hereinafter described, bears S. 69° 10' W., 5.64 chs. distance.