

## County Surveyor's Record, Douglas County, Oregon

## Subdivision of Section 13, T. 28 S., R. 4 W.

CHAINS	
	Ascend 175 ft. over E. slope, changing to S. E. slope.
25.83	Dirt road, 30 lks. wide, bears N. 80° E. and S. 80° W.
39.16	The center $\frac{1}{4}$ sec. cor. of sec. 13. Ascend 95 ft. over S. E. slope.
44.70	Spur, slopes S.; desc. 320 ft. over general W. slope, also enter dense undergrowth.
51.70	Dirt road, 20 lks. wide, bears N. and S.
56.00	North Myrtle Creek, 10 lks. wide, course S. 10° W.; asc. 55 ft. over N.E. slope.
58.99	Point for the center W $\frac{1}{16}$ sec. cor. of sec. 13 Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd. $\begin{array}{c} C \frac{W \frac{1}{16} C}{S \ 13} \\ 1965 \end{array}$ from which A fir, 7 ins. diam., bears N. 23° E., $\frac{9}{4}$ lks. dist., marked CW $\frac{1}{16}$ S13 BT. A fir, 15 ins. diam., bears S. 12° W., 26 lks. dist., marked CW $\frac{1}{16}$ S13 BT. Ascend 235 ft. over broken N.E. slope.
69.905	Point for the center W-W $\frac{1}{64}$ sec. cor. of secs. 13. Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 23 ins. in the ground, with brass cap mkd. $\begin{array}{c} S \ 13 \\ C-W-W \\ \frac{1}{64} \\ 1965 \end{array}$ from which A chinquapin, 9 ins. diam., bears N. 36° W., $\frac{9}{2}$ lks. dist., marked CWW $\frac{1}{64}$ BT. A fir, 4 ins. diam., bears S. 13° W., 13 lks. dist., marked X BT. Ascend 15 ft. over N.E. slope.
70.70	Spur, slopes N. 10° E.; desc. 30 ft. over N.W. slope.
71.90	Ravine, drains N. 10° E.; asc. 80 ft. over N.E. slope.
73.70	Spur, slopes N.; desc. 25 ft. over N.W. slope.
76.65	Creek, 1 lk. wide, from S. 60° W., course N. 25° E.; asc. 110 ft. over N. E. slope.
78.82	The $\frac{1}{4}$ sec. cor. of secs. 13 and 14.

From the E  $\frac{1}{16}$  sec. cor. of secs. 13 and 24.

N. 0° 04' E., on the N. and S. center line of SE  $\frac{1}{4}$  of sec. 13.